SIEMENS

Data sheet 3RT2926-5AM21



Magnet coil for contactors 18.5 kW 208 V AC, 50 / 60 Hz, for motor contactors, Size S0, Screw terminal

General technical data	
product brand name	SIRIUS
product designation	Magnet coil
Control circuit	
type of voltage of the control supply voltage	AC
power loss [V·A] of magnet coil at AC typical	10.5 V·A
control supply voltage	
● 1 at AC	
— at 50 Hz rated value	208 V
— at 60 Hz rated value	208 V
operating range factor control supply voltage rated value of magnet coil at AC	
● at 50 Hz	0.8 ... 1.1
● at 60 Hz	0.85 ... 1.1

Certificates/ approvals

General Product Approval	EMC	Declaration of Conformity	Shipping Approval
EAC	RCM	Miscellaneous	CE EG-Konf. BUREAU VERITAS RMRS

other

Confirmation

VDE

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2926-5AM21
Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2926-5AM21

Subject to change without notice
© Copyright Siemens

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RT2926-5AM21
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2926-5AM21&lang=en

last modified: 5/15/2020

Subject to change without notice
© Copyright Siemens