SIEMENS

Data sheet 3RT2926-5AT61



Magnet coil for contactors 18.5 kW 600 V AC, 60Hz, for motor contactors, Size S0, Screw terminal

General technical data	
product brand name	SIRIUS
product designation	Magnet coil
Control circuit	
type of voltage of the control supply voltage	AC
power loss [V·A] of magnet coil at AC typical	9.8 V·A
control supply voltage	
• 1 at AC	
— at 50 Hz rated value	660 V
operating range factor control supply voltage rated value of magnet coil at AC	
• at 50 Hz	0.8 ... 1.1
• at 60 Hz	0.85 ... 1.1

Certificates/ approvals

General Product Approval	EMC	Declaration of Conformity		Shipping Approval	
EAC	RCM	CE EG-Konf.	Miscellaneous	BUREAU VERITAS	RMRS

other

Confirmation

VDE

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2926-5AT61
Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2926-5AT61
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RT2926-5AT61

Subject to change without notice
© Copyright Siemens

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2926-5AT61&lang=en

last modified: 5/15/2020

Subject to change without notice
© Copyright Siemens