
SIEMENS

Data sheet 3RA6890-1AA

Extension connector for infeed system 3RV19, 3RV29



General technical data		
product brand name		SIRIUS
product designation		Expansion connector for 3RV19 / 3RV29
degree of pollution		3
installation altitude at height above sea level maximum	m	2 000
ambient temperature		
● during transport	°C	-55 ... +80
● during storage	°C	-55 ... +80
● during operation	°C	-20 ... +60
vibration resistance		f = 4 to 5.8 Hz; d = 15 mm; f = 5.8 to 500 Hz; a = 2 m / s2 10 cycles
shock resistance		Semi-sinusoidal a = 6 m/s2 at 10 ms; 3 pos. and 3 neg. Shock in all axes
reference code		
● acc. to IEC 81346-2		X
● acc. to DIN EN 61346-2		X
Main circuit		
operational current at AC at 400 V rated value	A	63
Installation/ mounting/ dimensions		
fastening method		plug-in fixing
width	mm	40
height	mm	55
depth	mm	100

Certificates/ approvals

General Product Approval	EMC	Declaration of Conformity

CSA UL EAC RCM Miscellaneous EG-Konf.

Test Certificates	Shipping Approval

Subject to change without notice
© Copyright Siemens

Type Test Certificates/Test Report

ABS BUREAU VERITAS LRS PRS RINA


Shipping Approval	other


RMRS Confirmation

Safety related data		
touch protection against electrical shock		finger-safe

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA6890-1AA
Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA6890-1AA
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RA6890-1AA
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA6890-1AA&lang=en





last modified: 1/6/2021

Subject to change without notice
© Copyright Siemens