SIEMENS

Data sheet 6ES7193-6AP40-0AA0



SIMATIC ET 200SP, BusAdapter: BA SCRJ/FC, Media converter FOC-CU 1x SCRJ FO connection and, 1x FastConnect (FC) connection for PROFINET

General information	
Product type designation	BA SCRJ/FC
HW functional status	from FS04
Interfaces	
Number of PROFINET interfaces	1; 2 ports (SCRJ + FC)
Supports protocol for PROFINET IO	
● Number of FC (FastConnect) connections	1
● Number of SCRJ ports	1
● Number of LC ports	0
Cable length	
— PCF	100 m
— Plastic FOC (POF)	50 m
— PCF-GI	250 m
— Cu conductors	100 m
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-25 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-25 °C
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m; On request: Installation altitudes greater than 2 000 m
Dimensions	
Width	20 mm
Height	69.5 mm
Depth	59 mm
Weights	
Weight, approx.	50 g

last modified: 3/5/2020

Subject to change without notice
© Copyright Siemens