SIEMENS

## Data sheet US2:DTNFC362R



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: CSA V. Rating: 600V A. Rating: 60A Wattage: 3W No. Of Poles: 3P F. Rating: 60Hz Action: DOUBLE THROW Material: 304SS Enclosure: TYPE 3R. 2-3 point mounting holes. O. Cycles: 10000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: OUTDOOR

| | |
|---|---|
| principle of operation of the actuating element | DOUBLE THROW |
| mechanical service life (switching cycles) typical | 10000 |
| fastening method | 2 OR 3 POINT MOUNTING HOLES |
| number of poles | 3 |
| ampacity | 60 A |
| supply voltage frequency rated value 50/60 Hz | Yes |
| voltage between phase and Ground (GND) rated value | 600 V |
| switching capacity active power | 3 W |
| product brand name | SIEMENS |
| product type designation | ENCLOSED/SAFETY SWITCH |
| design of the housing | TYPE 3R |
| material | Galv. Steel, Painted |
| certificate of suitability | CSA |

**last modified:** 1/6/2021


Subject to change without notice
© Copyright Siemens