ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

1160 MHz Cavity Bandpass Filter

Part Number: AB1160B514

ISO 9001 REGISTERED FIRM

Electrical specifications

Center Frequency: 1160 MHz
1 dB BW: 54 MHz min
Insertion loss in PB: 2 dB max
Return loss: 15 dB min
Rejection 1: 30 dBc@1115 MHz
Rejection 2: 30 dBc@1205 MHz


Mechanical

Mounting Method: Threaded Mounting Holes
Connector Type: N Female
Dimensions: 3.0 x 2.1 x 1.9 in

Environmental

Operating Temperature: -45 to +85° C
Storage Temperature: -55 to +95° C
Shock: 20 G. 11ms
Vibration: 20 G. 5 to 200 MHz

Outline Drawing:



70 Outwater Lane Phone: (973) 772-4242
Garfield, NJ 07026 Fax : (973) 772-4646
Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com


ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

1160 MHz Cavity Bandpass Filter

Part Number: AB1160B514

ISO 9001 REGISTERED FIRM

Plot:



70 Outwater Lane Phone: (973) 772-4242
Garfield, NJ 07026 Fax : (973) 772-4646
Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com