ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

1625 MHz Cavity Bandpass Filter

Part Number: AB1625B881

ISO 9001 REGISTERED FIRM

Electrical specifications

Center Frequency: 1625 MHz
Insertion loss @1625 MHz: =/<3 dB
Passband: 1613-1637 MHz
Rejection 1: 70 dB@ 1500 MHz
Rejection 2: 70 dB@ 1750 MHz


Mechanical

Mounting Method: Threaded Mounting Holes
Connector Type: SMA Female
Dimensions: 2.00 X 1.80” X 1.50” in

Environmental

Operating Temperature: -45 to +85º C
Storage Temperature: -55 to +95º C
Shock: 20 G. 11ms
Vibration: 20 G. 5 to 200 MHz

Outline Drawing:



70 Outwater Lane
Garfield, NJ 07026
Phone: (973) 772-4242
Fax : (973) 772-4646
Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com


ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

1625 MHz Cavity Bandpass Filter

Part Number: AB1625B881

ISO 9001 REGISTERED FIRM

Plot:



70 Outwater Lane Phone: (973) 772-4242
Garfield, NJ 07026 Fax : (973) 772-4646
Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com