ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

2330-2340 MHz Cavity Bandpass Filter

Part Number: AB2335B996

ISO 9001 REGISTERED FIRM

Electrical specifications

Center Frequency: 2335 MHz
Bandwidth: 10 MHz
Input / Output Impedance: 50 Ohms
Passband: 2330 – 2340 MHz
Passband variation over bandwidth: <0.5dB
Passband Insertion Loss: <1.0dB
Passband Ripple: <0.2 dB
Passband Return Loss: >20dB
Group delay variation over bandwidth: <5ns
Rejection: 13 MHz offset from Center Frequency >20dBc
Rejection 2: 20 MHz offset from Center Frequency >30dBc
Power Handling: 20 Watts
Peak Power Handling: 150 Watts


Mechanical

Mounting Method: Threaded Mounting Holes
Connector Type: SMA Female
Dimensions: 6.69 x 5.51 x 2.13 in.

Environmental

Operating Temperature: 0 to +55 deg.C
Storage Temperature: -55 to +95 deg.C
Shock: 20 G. 11ms
Vibration: 20 G. 5 to 200 MHz

Outline Drawing:



70 Outwater Lane
Garfield, NJ 07026
Phone: (973) 772-4242
Fax : (973) 772-4646
Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com


ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

2330-2340 MHz Cavity Bandpass Filter

Part Number: AB2335B996

ISO 9001 REGISTERED FIRM

Response Plot:



70 Outwater Lane Phone: (973) 772-4242
Garfield, NJ 07026 Fax : (973) 772-4646

Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com