ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

2355 MHz Cavity Bandpass Filter

Part Number: AB2355B1008

ISO 9001 REGISTERED FIRM

Electrical specifications

Frequency band: 2345-2365 MHz
Passband: 2345.4-2364.6 MHz
Insertion loss: <1.0 dB
Passband Variation: 0.7 dB
S11&S12:>-20 dB
Attenuation: 12 dB@12.5 MHz
Group delay: 80 nS
Power Handling: 20 W average, 200 peak power


Mechanical

Mounting Method: Threaded Mounting Holes
Connector Type: SMA Female
Dimensions: 6.60” X 4.45” X 1.52” in

Environmental

Operating Temperature: -45 to +85º C
Storage Temperature: -55 to +95º C
Shock: 20 G. 11ms
Vibration: 20 G. 5 to 200 MHz

Outline Drawing:



70 Outwater Lane
Garfield, NJ 07026
Phone: (973) 772-4242
Fax : (973) 772-4646
Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com


ANATECH ELECTRONICS INC
RF & Microwave Filters & Products


2355 MHz Cavity Bandpass Filter

Part Number: AB2355B1008

ISO 9001 REGISTERED FIRM

Plot:





70 Outwater Lane
Garfield, NJ 07026
Phone: (973) 772-4242
Fax : (973) 772-4646
Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com