Product data sheet

Specifications



terminal block

AB3RV162U

Complementary

[In] rated current	150 A for 1P busbar
Electrical connection	1 solid upstream 35 mm² connector 1 flexible upstream 25 mm² connector 6 solid downstream 0.5…6 mm² tap-off 6 flexible downstream 0.5…4 mm² tap-off
Fixing mode	Clip-on
Mounting support	rail
Product compatibility	Universal fixing frames
Product destination	terminal block

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.500 cm
Package 1 Width	12.700 cm
Package 1 Length	15.500 cm
Package 1 Weight	91.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	13.500 cm
Package 2 Width	12.700 cm
Package 2 Length	15.500 cm
Package 2 Weight	917.000 g
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Height	15.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	3.970 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Recommended replacement(s)