trumeter
innovation by design




MicroAMP Meter

For DC Current Measurement

EVALUATION KIT AVAILABLE
Contact us to request yours

THREE YEAR 3 WARRANTY

Easy to Use. Easy to Read.



Featuring an acclaimed easy-to-read display and a high resolution input, the MicroAMP Meter is the ideal meter for applications where accurate DC current measurement is required.

With an accurate 0-200uA DC input, the APM MicroAMP is ideal for DC current measurement applications in marine, leisure, material handling, and industrial applications such as power supplies, load banks and charging systems.

The programmable scale and custom annunciators mean users can tailor the meter to display their critical parameters exactly how they want. Dynamic backlighting, in conjunction with setpoints, means operators are visually alerted when a parameter is out of range while the two outputs can be used to connect the APM to other systems in the process, meaning the MicroAMP is much more than just a display.

Go to www.trumeter.com/apm for further information

trumeter
innovation by design

custom is our passion

Key Features

Unique Display

- 40 segment bar graph display
- Large 4-digit display
- Separate Starburst display area for annunciators, custom messages and alarm information
- Dynamic backlight color


Visibility

- User-adjustable backlight brightness and colour
- Large display
- Wide viewing angle (horizontal and vertical)
- Custom annunciators

Programmable

- Scale (offset, gain andlinear) and Range (min and max)
- User selectable backlight color and intensity
- ***NEW*** 20 point non-linearization scaling for non-linear sensors e.g. thermocouples and pressure transducers
- ***NEW*** Ten independent alarm set-points
- ***NEW*** Configurable digital output delays (control the time output stays open/closed - .5 seconds – 120 seconds)

Dimensions:




Panel cutout: 68mm x 68mm [2.68" x 2.68"] as per DIN43700/IEC61554

INPUT	
Range	0-200uA DC
Impedance	4700Ω
Accuracy	0.01% of input or 0.5uA whichever is greater
ENVIRONMENTAL	
Temperature - operating	-10 to +60°C
Temperature - storage	-40 to +70°C
IP rating (from the front)	IP65
NEMA rating (from the front)	Type 4 & Type 12
POWER SUPPLY	
Nominal Input	12-24 VDC
DISPLAY	
Number of digits	4
Digit height	12mm [0.47"]
Number of message characters	4
Backlight colors	Red, Green, White
LCD display	Positive or Negative
OUTPUTS	
Max voltage	34V
Max current	500mA
Analog output	4-20mA
CERTIFICATION	UL, cUL, CE, UKCA

Easy To Use Software

Just plug into any USB port on your PC, run the freely available APM Configurator application and you're off. No drivers required.



c UL us LISTED Open-type Measuring and Testing Equipment E469787

Part Numbers:

APM-MICRO-APO	APM MicroAMP Meter, Postive LCD with outputs
APM-MICRO-ANO	APM MicroAMP Meter, Negative LCD with outputs
022128-01	USB Cable
022150-01	APM Evaluation Kit

By Request: Modbus© connectivity

APM-MICRO-APS	APM MicroAMP Meter, Postive LCD with Modbus©
APM-MICRO-ANS	APM MicroAMP Meter, Negative LCD with Modbus©

Full specifications available online **www.trumeter.com/apm**



www.trumeter.com

Trumeter (The Americas)
6601 Lyons Rd, Suite H-7
Coconut Creek, Florida
FL 33073,
USA
Tel: +1 954 725 6699
Email: sales.usa@trumeter.com

Trumeter (Europe)
Trumeter
Pilot Mill, Alfred Street
Bury, Lancashire
BL9 9JR
Tel: +44 161 674 0960
Email: sales.uk@trumeter.com

Innovative Design Technologies Sdn. Bhd
Lot 5881, Lorong Iks Bukit Minyak 1
Taman Perindustrian Iks, 14000 Bukit Tengah
Penang, Malaysia
Web: www.idtworld.com
Tel: + 604 5015700
Email: sales.my@idtworld.com