Oct.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

Applicable standard				
Rating	Operating temperature range	-55°C to + 85°C(Note 1)	Storage temperature range	-10°C to + 60°C(Note2)
	Operating humidity range	20% to 80% (Note3)	Storage humidity range	40% to 70%(Note2)
	Voltage	AC 1000V DC	Applicable Connector	DF22-*(D)EP-7.92C DF22#-*(D)EP-7.92C
	Current(*1)	AWG14 :20A AWG16 :15A	Applicable cable	UL1015 AWG14,16

	Rated voltage	Rated current	Overvoltage category	IP-Protection method
UL	AC 600V	AWG14:26A/AWG16:21A (At ambient temp.25°C)	—	—
C-UL	AC 600V	See above(*1) (Temp. rise up 30°C MAX)	—	—
TÜV	AC 600V	See above(*1)	Ⅱ	IPOO

Specifications

Item	Test method	Requirements	QT	AT
Construction				
General examination	Visually and by measuring instrument.	According to drawing.	X	X
Marking	Confirmed visually.		X	X
Electric characteristics				
Contact resistance millivoltlevel method	20mV MAX, 1mA (DC OR 1000 Hz).	5 mΩ MAX.	X	—
Mechanical characteristics				
Mechanical operation	50 times insertions and extractions.	① Contact resistance: 10mΩ MAX. ② No damage, crack or looseness of parts.	X	—
Vibration	Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 2 h, for 3 directions.	① No electrical discontinuity of 1μs. ② No damage, crack or looseness of parts.	X	—
Shock	490 m/s^2 duration of pulse 11 ms at 3 times for 3 directions.	① No electrical discontinuity of 1μs. ② No damage, crack or looseness of parts.	X	—
Environmental characteristics				
Rapid change of temperature	Temperature -55→ 5 to 35→+85→ 5 TO 35 °C Time 30→ 5 MAX → 30→ 5 MAX min Under 5 cycles.	① Contact resistance: 10mΩ MAX. ② No damage, crack or looseness of parts.	X	—
Damp heat (Steady state)	Exposed at 40 ± 2 °C, 90 to 95 %, 96 h.	① Contact resistance: 10mΩ MAX. ② No damage, crack or looseness of parts.	X	—

Remarks
Note 1: Including the temperature rising by current.
Note 2: No condensing.
Note 3: Apply to the condition of long term storage for unused products before harness assembly.
After harness assembly, operation temperature and humidity range is applied for interim storage during transportation.

	Count	Description of revisions	Designed	Checked	Date
⚠0					

Unless otherwise specified, refer to IEC 60512.

Approved	HS. OKAWA	20190731
Checked	SZ. ONO	20190731
Designed	TS. KUMAZAWA	20190731
Drawn	TS. KUMAZAWA	20190731

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

Drawing no. ELC-388483-00-00

HRS	Specification sheet	Part no.	DF22A-1416PCFA	
	HIROSE ELECTRIC CO., LTD.	Code no.	CL680-1194-0-00	⚠0 1/1

FORM HD0011-2-1