




Click [here](#) for the 3D model.

| Dimensions  |                |
|-------------|----------------|
| D           | 16mm +/-0.5mm  |
| L           | 20mm +2.0mm    |
| S           | 7.5mm +/-0.5mm |
| LL Negative | 15mm MIN       |
| LL Positive | 20mm MIN       |
| F           | 0.8mm NOM      |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |

| General Information |                                    |
|---------------------|------------------------------------|
| Series              | ETA                                |
| Dielectric          | Aluminum Electrolytic              |
| Description         | Single Ended Aluminum Electrolytic |
| RoHS                | Yes                                |
| Lead                | Wire Leads                         |
| AEC-Q200            | No                                 |

| Specifications          |                          |
|-------------------------|--------------------------|
| Capacitance             | 1,200 uF                 |
| Capacitance Tolerance   | 20%                      |
| Voltage DC              | 35 VDC, 44 VDC (Surge)   |
| Temperature Range       | -40/+105°C               |
| Rated Temperature       | 105°C                    |
| Life                    | 10000 Hrs                |
| Dissipation Factor      | 12%                      |
| Resistance              | 0.027 Ohms (100kHz 20C)  |
| Ripple Current          | 2530 mAmps (100kHz 105C) |
| Leakage Current         | 420 uA (2min)            |
| Impedance Ratio at -25C | 2                        |
| Impedance Ratio at -40C | 3                        |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.