ATGBICS

ATGBICS GLC-ZX-SM-C network transceiver module Fiber optic 1000 Mbit/s SFP 1550 nm

Brand : ATGBICS

Product code: GLC-ZX-SM-C

Product name : GLC-ZX-SM-C



Cisco Compatible Transceiver SFP 1000Base-ZX 1550nm SMF 80km

ATGBICS GLC-ZX-SM-C network transceiver module Fiber optic 1000 Mbit/s SFP 1550 nm:

ATGBICS GLC-ZX-SM 1000Base-ZX supports a distance of up to 80km over single mode fibre (SMF) using a wavelength of 1550nm via an LC connector. Our product is built to the exact specification of Cisco GLC-ZX-SM= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards. ATGBICS GLC-ZX-SM-C. SFP transceiver type: Fiber optic, Maximum data transfer rate: 1000 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 0.8 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box

Performance	
SFP transceiver type *	Fiber optic
Maximum data transfer rate *	1000 Mbit/s
Interface type *	SFP
Single-mode fiber (SMF) supported	✓
Multi-mode fiber (MMF) supported	✗
Fiber optic connector	LC
SFP transceiver standard	ZX
Maximum transfer distance	80000 m
Wavelength	1550 nm
Ethernet LAN	✓
Ethernet interface type	Fast Ethernet
Digital Diagnostics Monitoring (DDM)	✗
Wavelength-division multiplexing (WDM)	✗

Features	
Product colour	Silver
Housing material	Metal
Plug and Play	✓
Hot-Plug support	✓
Hot-swap	✓
Easy to install	✓

Features	
Country of origin	United Kingdom
Brand compatibility	Cisco

Power	
Input voltage	3.3 V
Maximum voltage	3.5 V
Power consumption (typical)	0.8 W

Operational conditions	
Maximum operating temperature	70 °C
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions	
Width	13.4 mm
Depth	56.5 mm
Height	8.5 mm
Weight	15 g

Packaging data	
Number of products included	1 pc(s)
Package type	Box

Technical details	
Sustainability certificates	RoHS



5056468706263

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-OCT-2022. Prints or copies of Information are only valid on the printed Publication date