Oct.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	FREQUENCY RANGE	DC ～ 50 GHz	STORAGE TEMPERATURE RANGE	-55℃～+ 125℃(No Load) (※1)
	POWER	1 W CW (AT 65℃)	CHARACTERISTIC IMPEDANCE	5 0 Ω
	OPERATING TEMPERATURE RANGE	−10 ℃ TO +65 ℃	APPLICABLE CABLE	---
	OPERATING RELATIVE HUMIDITY	～ 90 %	USED CONNECTOR	H2.4-P , H2.4-J

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
ELECTRIC CHARACTERISTICS				
V.S.W.R	MUST BE UNDER THE STD.VALUE AT FREQENCY DC TO 50 GHz	1.35 MAX (DC ～ 12 GHz) 1.4 MAX (12 ～ 50GHz)	X	X
INSERTION LOSS	MUST BE UNDER THE STD.VALUE AT FREQENCY DC TO 50 GHz	19 dB ～21 dB (DC ～18GHz) 19 dB ～21.2 dB (18 ～26.5GHz) 19 dB ～21.4 dB (26.5 ～50GHz)	X	X
INSULATION RESISTANCE	MUST BE OVER STANDARD VALUE AT DC V.	MINIMUM OF MΩ	—	—
VOLTAGE PROOF	V AC FOR 1 min.CURRENT LEAKAGE 2mA MAX.	NO FLASHOVER OR BREAKDOWN.	—	—
RESISTANCE VALUE	MEASURE THE RESISTANCE VALUE AT DC V.	MAX	—	—
MECHANICAL CHARACTERISTICS				
MECHANICAL OPERATION	500 TIMES INSERTIONS AND EXTRACTIONS.	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF	X	—
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm OR 1 oct/min AT 10 CYCLES FOR 3 DIRECTIONS.	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X	—
SHOCK	490 m/s^2 AT 18 TIMES FOR 3 DIRECTIONS.	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X	—
ENVIRONMENTAL CHARACTERISTICS				
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → 15～25 → 125 → 15～25 ℃ TIME 30 → 2～3 → 30 → 2～3 min UNDER 100 CYCLES.	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO HEAVY CORROSION.	X	—
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ℃, 90% TO 95% TOTAL 96 h.	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO HEAVY CORROSION.	X	—
DRY HEAT	EXPOSED AT 125 ℃ TOTAL 48 h.	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO HEAVY CORROSION.	X	—
COLD	EXPOSED AT -55 ℃ TOTAL 48 h.	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO HEAVY CORROSION.	X	—
CORROSION SALT MIST	EXPOSED IN 5±1 % SALT WATER , AT 35±2℃ SPRAY FOR 48 HOURS.	1.35 MAX (DC ～ 12 GHz) 1.4 MAX (12 ～ 50GHz)	X	—

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
⓪					

REMARKS RoHS COMPLIANT
High frequency performance is only measured and the data is not attached.
(※1) The storage temperature range means the one of the product itself without packaging.
Unless otherwise specified, refer to IEC 60512.

APPROVED	KH. IKEDA	18.02.08
CHECKED	TS. NOBE	18.02.08
DESIGNED	HA. NISHIMURA	18.02.08
DRAWN	HA. NISHIMURA	18.02.08

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC-381496-00-00

HRS	SPECIFICATION SHEET	PART NO.	H2.4-AT(20)-PJ	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL354-0294-0-00 ⓪	1/1

FORM HD0011-2-1