



Figure similar

Electrically held lighting contactor, Contactor amp rating 20A, 0 N.C. / 4 N.O. Poles, 347VAC 60HZ coil, Non-combination type, (no disconnect device), Enclosure NEMA type 12, Dust/drip proof for indoors

product brand name
design of the product
special product feature

Class LE
Electrically held lighting contactor
Compact design; Finger safe control terminals

General technical data

weight [lb] 17 lb
Height x Width x Depth [in] 16 × 13 × 6 in
touch protection against electrical shock NA for enclosed products
installation altitude [ft] at height above sea level maximum 6560 ft
ambient temperature [°F]
 • during storage -67 ... +176 °F
 • during operation 32 ... 104 °F
ambient temperature
 • during storage -55 ... +80 °C
 • during operation 0 ... 40 °C
country of origin USA



Contactor

size of contactor 20 Amp
number of NO contacts for main contacts 4
number of NC contacts for main contacts 0
operating voltage for main current circuit at AC at 60 Hz maximum 600 V
mechanical service life (operating cycles) of the main contacts typical 30000000
contact rating of the main contacts of lighting contactor
 • at electronic ballast [LED driver] (1 pole per 1 phase) rated value 8A @120V / 3A @277V 1p 1ph
 • at tungsten (1 pole per 1 phase) rated value 20A @277V 1p 1ph
 • at tungsten (2 poles per 1 phase) rated value 20A @480V 2p 1ph
 • at tungsten (3 poles per 3 phases) rated value 20A @480V 3p 3ph
 • at ballast (1 pole per 1 phase) rated value 20A @347V 1p 1ph
 • at ballast (2 poles per 1 phase) rated value 20A @600V 2p 1ph
 • at ballast (3 poles per 3 phases) rated value 20A @600V 3p 3ph
 • at resistive load (1 pole per 1 phase) rated value 20A @600V 1p 1ph
 • at resistive load (2 poles per 1 phase) rated value 20A @600V 2p 1ph
 • at resistive load (3 poles per 3 phases) rated value 20A @600V 3p 3ph

Auxiliary contact

number of NC contacts at contactor for auxiliary contacts 0
number of NO contacts at contactor for auxiliary contacts 1
number of total auxiliary contacts maximum 4
contact rating of auxiliary contacts of contactor according to UL A600 / Q600

Coil	
type of voltage of the control supply voltage	AC
control supply voltage	
• at AC at 60 Hz rated value	347 V
apparent pick-up power of magnet coil at AC	31.7 VA
apparent holding power of magnet coil at AC	4.8 VA
operating range factor control supply voltage rated value of magnet coil	0.85 ... 1.1
Enclosure	
degree of protection NEMA rating of the enclosure	NEMA 12 enclosure
design of the housing	dustproof and drip-proof for indoor use
Mounting/wiring	
mounting position	Vertical
fastening method	Surface mounting and installation
type of electrical connection for supply voltage line-side	Screw-type terminals
tightening torque [lbf-in] for supply	7 ... 12 lbf-in
type of connectable conductor cross-sections at line-side at AWG cables single or multi-stranded	2x (20 ... 16 AWG), 2x (18 ... 14 AWG), 2x 12 AWG
temperature of the conductor for supply maximum permissible	75 °C
material of the conductor for supply	CU
type of electrical connection for load-side outgoing feeder	Screw-type terminals
tightening torque [lbf-in] for load-side outgoing feeder	7 ... 12 lbf-in
type of connectable conductor cross-sections at AWG cables for load-side outgoing feeder single or multi-stranded	2x (20 ... 16 AWG), 2x (18 ... 14 AWG), 2x 12 AWG
temperature of the conductor for load-side outgoing feeder maximum permissible	75 °C
material of the conductor for load-side outgoing feeder	CU
type of electrical connection of magnet coil	Screw-type terminals
tightening torque [lbf-in] at magnet coil	7 ... 10 lbf-in
type of connectable conductor cross-sections of magnet coil at AWG cables single or multi-stranded	2x (20 ... 16 AWG), 2x (18 ... 14 AWG)
temperature of the conductor at magnet coil maximum permissible	75 °C
material of the conductor at magnet coil	CU
type of electrical connection at contactor for auxiliary contacts	Screw-type terminals
tightening torque [lbf-in] at contactor for auxiliary contacts	7 ... 12 lbf-in
type of connectable conductor cross-sections at contactor at AWG cables for auxiliary contacts single or multi-stranded	2x (20 ... 16 AWG), 2x (18 ... 14 AWG)
temperature of the conductor at contactor for auxiliary contacts maximum permissible	75 °C
material of the conductor at contactor for auxiliary contacts	CU
Short-circuit current rating	
design of the fuse link for short-circuit protection of the main circuit required	100kA@600V (Class RK5 30A max)
design of the short-circuit trip	Thermal magnetic circuit breaker
maximum short-circuit current breaking capacity (Icu)	
• at 240 V	24 kA
• at 480 V	5 kA
• at 600 V	5 kA
certificate of suitability	NEMA ICS 2; UL 508
Further information	
Industrial Controls - Product Overview (Catalogs, Brochures,...) www.usa.siemens.com/iccatalog	
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:LEN02B004347B	
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/US/en/ps/US2:LEN02B004347B	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:LEN02B004347B&lang=en	
Certificates/approvals https://support.industry.siemens.com/cs/US/en/ps/US2:LEN02B004347B/certificate	



LEN00B004 Wiring Diagram

D38309002

last modified:

4/5/2023

