

FLAT PANEL DIRECTIONAL ANTENNA

PA24

2400-2483 MHZ OPERATION FLAT PANEL DIRECTIONAL ANTENNA

The 2.4 GHz flat panel directional antennas by Laird offer high gain in a thin low profile package. The antennas are constructed of a gray color UV resistant ABS plastic radome with an aluminum backplate. The antenna can be used in horizontal or vertical polarization. The die cast aluminum or galvanized steel bracket affords +/- 45 deg up or down tilt adjustment and the stainless steel hardware assures a long service life. The PA24-13 and PA24-19 antenna can be surface mounted or pole mounted. The PA24-16 is pole mounted only. All antennas comes with an integral N female connector standard.


FEATURES RoHS

- High gain / low profile
- Pole mount or surface mount
- Rugged and weatherproof
- Vertical or horizontal polarization
- Type N female connector


MARKETS

- Wireless LAN applications
- Client antennas
- 802.11b/g applications
- OEM wireless data
- WiMAX


ANTENNA PATTERNS



PA24-13



PA24-16



PA24-19

SPECIFICATIONS

PARAMETER	PA24-13	PA24-16	PA24-19
Frequency range	2400 - 2483 MHz	2400 - 2483 MHz	2400 - 2483 MHz
Gain	13 dBi	16 dBi	19 dBi
3dB beamwidth (H & V)	35°	26°	17.5°
Front to back	20 dB	27 dB	30 dB
Cross polarization	-20 dB	-20 dB	-20 dB
VSWR	1.5:1	1.5:1	1.5:1
Impedance	50 ohm	-	50 ohm
Input power	100 watts	-	100 watts
Operating temperature	-40° to +70°C	-40° to +70°C	-40° to +70°C
Pole size	1 to 2 in (25 to 50 mm)	1 to 2 in (25 to 50 mm)	1 to 2 in (25 to 50 mm)
Weight	17.6 oz (0.5 kg)	31.5 oz (0.9 kg)	60 oz (1.7 kg)
Dimension (dia x depth)	.5 x 7.5 x 0.8 in (190 x 190 x 20 mm)	11 x 11 x 0.8 in (279 x 279 x 20 mm)	15.3 x 14.6 x 0.8 in (389 x 368 x 20 mm)
Bracket tilt	45°	45°	45°

WIND LOADING (LBS.)

MODEL	SQ. IN	100 MPH	125 MPH	100 MPH WITH ½ IN RADIAL ICE
PA24-13	56	14 lbs	22 lbs	14 lbs
PA24-16	121	30 lbs	47 lbs	32 lbs
PA24-19	163	41 lbs	64 lbs	41 lbs

SYSTEM ORDERING

PA24-13 2.4 GHz 13 dBi flat panel directional antenna PA24-16 2.4 GHz 16 dBi flat panel directional antenna PA24-19 2.4 GHz 19 dBi flat panel directional antenna

NOTES

•All shipments F.O.B. Schaumburg, IL 60173

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

©2021 TE Connectivity. All Rights Reserved.

11/21 Original