ATGBICS

ATGBICS PAN-SFP-CG-C network transceiver module Copper 1250 Mbit/s

Brand : ATGBICS

Product code: PAN-SFP-CG-C

Product name : PAN-SFP-CG-C



Palo Alto Compatible Transceiver SFP 10/100/1000Base-T Copper RJ45 Connector 100m

ATGBICS PAN-SFP-CG-C network transceiver module Copper 1250 Mbit/s:

ATGBICS PAN-SFP-CG SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Palo Alto 1000BASE-T SFP modules support 10/100/1000 auto negotiation and auto MDI/MDIX. Our product is built to the exact specification of Palo Alto PAN-SFP-CG= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.
ATGBICS PAN-SFP-CG-C. SFP transceiver type: Copper, Maximum data transfer rate: 1250 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Width: 13.4 mm, Depth: 56.6 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box

Performance	
SFP transceiver type *	Copper
Maximum data transfer rate *	1250 Mbit/s
Interface type *	SFP
Single-mode fiber (SMF) supported	✗
Multi-mode fiber (MMF) supported	✗
SFP transceiver standard	TX
Maximum transfer distance	100 m
Ethernet LAN	✓
Ethernet interface type	Gigabit Ethernet
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-TX
Auto MDI/MDI-X	✓
Digital Diagnostics Monitoring (DDM)	✗

Features	
Product colour	Silver
Housing material	Metal
Plug and Play	✓
Hot-Plug support	✓
Hot-swap	✓
Easy to install	✓
Country of origin	United Kingdom

Features	
Brand compatibility	Palo Alto Networks

Power	
Input voltage	3.3 V
Maximum voltage	4 V
Power consumption (typical)	1.3 W

Operational conditions	
Maximum operating temperature	70 °C
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 85%
Storage relative humidity (H-H)	5 - 85%

Weight & dimensions	
Width	13.4 mm
Depth	56.6 mm
Height	8.5 mm
Weight	24 g

Packaging data	
Number of products included	1 pc(s)
Package type	Box

Technical details	
Sustainability certificates	RoHS



5056468701107

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-OCT-2022. Prints or copies of Information are only valid on the printed Publication date