


## PME264NE6100MR30

Aliases (P264EL104M660A)

PME264/P264, Film, Metallized Paper, Safety, 0.1 uF, 20%, 660 VAC (X2), 1500 VDC, 85°C, Lead Spacing = 25.4mm



Click [here](#) for the 3D model.

| General Information |                  |
|---------------------|------------------|
| Series              | PME264/P264      |
| Dielectric          | Metallized Paper |
| Style               | Radial           |
| Features            | EMI Safety       |
| RoHS                | Yes              |
| Lead                | Wire Leads       |
| Safety Class        | X2               |
| Qualifications      | ENEC, UL, cUL    |
| AEC-Q200            | No               |
| THB Performance     | No               |
| Construction        | Molded           |
| Component Weight    | 13.5 g           |

| Dimensions |                 |
|------------|-----------------|
| L          | 30.5mm MAX      |
| H          | 22mm MAX        |
| T          | 15.3mm MAX      |
| S          | 25.4mm +/-0.4mm |
| LL         | 30mm +5mm       |
| F          | 1mm NOM         |

| Specifications        |              |
|-----------------------|--------------|
| Capacitance           | 0.1 uF       |
| Capacitance Tolerance | 20%          |
| Voltage AC            | 660 VAC (X2) |
| Voltage DC            | 1500 VDC     |
| Temperature Range     | -40/+85°C    |
| Rated Temperature     | 85°C         |
| Dissipation Factor    | 1.3% 1kHz    |
| Insulation Resistance | 12 GOhms     |
| Max dV/dt             | 600 V/us     |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 75        |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.