



FEATURES










- ## APPLICATIONS

- ## PRODUCT IDENTIFICATION






SHAPE AND DIMENSIONS

SLFB15-2R450G-02TF	Dimensions and Land Patterns   <Top View> 0.18 ± 0.10 0.54 ± 0.05 1.00 ± 0.05 0.30 ± 0.03 <Bottom View> 0.25 ± 0.10 (1) (2) (3) (1)(3) : GND (2) : Output/Input (4) : Input/Output A : MARK Unit:mm <Side View> 0.60 0.10 0.25 1.45 0.225 LATE INKING
SLFB15-2R450G-31TF	Dimensions and Land Patterns   <Top View> 1.0 ± 0.1 (1) M (3) (2) 0.6 ± 0.1 (1) : In / Out (2) : GND (3) : In / Out (4) : GND M : MARK Unit : mm <Bottom View> 0.3 ± 0.1 0.1 ± 0.05 0.1 ± 0.05 <Side View> 0.4 ± 0.05 0.3 ± 0.1

SHAPE AND DIMENSIONS

Type: SLFB18 Series	Dimensions and Land Patterns
	 
SLFB18-2R450G-31/36TF/ SLFB18-3R800G-01/03TF/ SLFB18-4R700G-03TF	Dimensions and Land Patterns
	<Top View> <Bottom View> <Side View>    (1) (3): In/Out (2): GND M: MARK Unit:mm
SLFB18-5R500G-33/34/38/39TF/ SLFB18-5R900G-01TF	Dimensions and Land Patterns
	<Top View> <Bottom View> <Side View>    (1) (3): In/Out (2): GND M: MARK Unit:mm
SLFB19-2R450G-03TF	Dimensions and Land Patterns
	<Top View> <Bottom View> <Side View>    (1) : Input (2) (3) (5): GND (4) : Out M : MARK Unit : mm

SHAPE AND DIMENSIONS

Type: SLFB21 Series	Dimensions and Land Patterns
	 (1) 2.00±0.15 (2) 0.25±0.15 (3) 1.70±0.15 (4) 1.20±0.15 0.85±0.10 0.30±0.15 0.75 1.50 0.95 0.75 0.35 Land Unit:mm
SLFB21-2R450G-31/33TF SLFB21-3R600G-41TF/ SLFB21-3R800G-17TF/ SLFB21-4R700G-19TF/ SLFB21-4R900G-31TF	Dimensions and Land Patterns
	<Top View> <Bottom View> <Side View>  (1) (3):In/Out (2):GND M:MARK Unit:mm
Type: SLFB22 Series	Dimensions and Land Patterns
	 (3) (6):In/Out (1)(2)(4)(5):GND M:MARK Unit:mm
Type: SLFB32 Series	Dimensions and Land Patterns
	<Top view> <Bottom view>  (1):IN (2):GND (3):OUT M:MARK Unit:mm

SPECIFICATIONS

SLFB15 TYPE

Part Number	Center Frequency	Pass Band	Max. IL in PB (at 25°C)	Attenuation	Thickness
Units	MHz	MHz	dB	dB	MM
Symbol	f_0	PB	IL	-	T
SLFB15-2R450G-02TF	2450	$f_0 \pm 50.0$	1.4	25 dB Min. at 880~960MHz	0.38±0.05
				8.0 dB Min. at 1710~1970MHz	
				23 dB Min. at 4800~5000MHz	
				32dB Min. at 7200~7500MHz	
SLFB15-2R450G-31TF	2450	$f_0 \pm 50.0$	1.3	9 dB Min. at DC~915 MHz	
				34 dB Min. at 4800~5000 MHz	
				27 dB Min. at 7200~7500 MHz	

SLFB18 TYPE

Part Number	Center Frequency	Pass Band	Max. IL in PB (at 25°C)	Attenuation	Thickness
Units	MHz	MHz	dB	dB	MM
Symbol	f_0	PB	IL	-	T
SLFB18-1R910G-01TF	1910	1805~2025	1.65	30 dB at 700~950MHz	0.80±0.10
				15 dB at 950~1050MHz	
				25 dB at 2400~2500MHz	
				35 dB at 2700~5400MHz	
				20 dB at 5500~12500MHz	
SLFB18-1R950G-31TF	1950	1880~2025	2.1	30 dB at 700~950MHz	
				28 dB at 950~1050MHz	
				20 dB at 1545~1610MHz	
				23 dB at 2400~2500MHz	
				20 dB. at 2700~5150MHz	
				25 dB at 5150~5850MHz	
SLFB18-2R450G-07TF	2450	2400~2500	1.8	30 dB Min. at 800~960MHz	
				30 dB Min. at 1710~1990MHz	
				30 dB Min. at 4800~5000MHz	
				30 dB Min. at 7200~7500MHz	
SLFB18-2R450G-31TF	2450	$f_0 \pm 50.0$	0.95	20 dB at 500~960MHz	
				23 dB at 3200~3312MHz	
				30 dB at 4800~5000MHz	
				32 dB at 7200~7500MHz	
SLFB18-2R450G-32TF	2495	2300~2690	2.0	12 dB Min. at 500~1800MHz	
				25 dB Min. at 3600~4000MHz	
SLFB18-2R450G-36TF	2450	2400~2500	0.95	20 dB at 500~960MHz	
				23 dB at 3200~3312MHz	
				30 dB at 4800~5000MHz	
				32 dB at 7200~7500MHz	
SLFB18-3R800G-01TF	3800	3300~4200	1.5	30 dB Min. at DC~693MHz	
				30 dB Min. at 693~2300MHz	
				30 dB Min. at 2300~2690MHz	
				18 dB Min. at 5150~5470MHz	
				25 dB Min. at 5470~5925MHz	
				25 dB Min. at 6600~8400MHz	
				25 dB Min. at 9900~12600MHz	

SPECIFICATIONS

SLFB18 TYPE

Part Number	Center Frequency	Pass Band	Max. IL in PB (at 25°C)	Attenuation	Thickness
Units	MHz	MHz	dB	dB	MM
Symbol	f_0	PB	IL	-	T
SLFB18-4R700G-03TF	4700	4400~5000	1.5	38 dB Min. at DC~693MHz	0.55±0.10
				38 dB Min. at 693~2690MHz	
				12 dB Min. at 5470~5735MHz	
				18 dB Min. at 5735~5925MHz	
				27 dB Min. at 8800~10000MHz	
				25 dB Min. at 13200~15000MHz	
SLFB18-3R800G-03TF	3800	3300~4200	1.9	38 dB Min. at DC~693MHz	
				38 dB Min. at 693~2300MHz	
				36 dB Min. at 2300~2690MHz	
				20 dB Min. at 5150~5470MHz	
				25 dB Min. at 5470~5925MHz	
				25 dB Min. at 6600~8400MHz	
SLFB18-5R500G-01TF	5512.5	$f_0 \pm 362.5$	1.5	30 dB Min. at 800~3800MHz	
				15 dB Min. at 10000~12000MHz	
SLFB18-5R500G-31TF	5512.5	$f_0 \pm 362.5$	1.5	33 dB at 100~2170MHz	
				29 dB at 2170~2500MHz	
				15 dB at 6900~7000MHz	
				16 dB at 7000~7200MHz	
				16 dB at 7200~7800MHz	
				32 dB at 9800~12000MHz	
SLFB18-5R500G-33TF	5500	5150~5925	1.5	35 dB at 700~2690MHz	
				28 dB at 3300~4200MHz	
				3.5 dB at 4400~4600MHz	
				0.5 dB at 5950~6000MHz	
				0.5 dB at 6000~6900MHz	
				15 dB at 6900~7200MHz	
				20 dB at 7200~9800MHz	
				20 dB at 9800~11700MHz	
				35 dB at 14700~17850MHz	
SLFB18-5R500G-34TF	5425	5000~5850	1.5	35 dB at 700~2690MHz	
				10 dB at 6900~72000MHz	
SLFB18-5R500G-36TF	5370	4900~5840	1.5	33 dB Min. at 100~2170MHz	0.65±0.10
				29 dB Min. at 2170~2500MHz	
				15 dB Min. at 6900~7800MHz	
				32 dB Min. at 9800~12000MHz	
SLFB18-5R500G-38TF	5550	5150~5950	0.8	35 dB at 30~2700MHz	0.55±0.10
				30 dB at 3400~3800MHz	
				15 dB at 7200~7800MHz	
				20 dB at 10300~11700MHz	

SPECIFICATIONS

SLFB18 TYPE

Part Number	Center Frequency	Pass Band	Max. IL in PB (at 25°C)	Attenuation	Thickness
Units	MHz	MHz	dB	dB	MM
Symbol	f ₀	PB	IL	-	T
SLFB18-5R900G-01TF	5900	5855~5925	1.1	35 dB at 100~2700MHz	0.70±0.1
				30 dB at 2700~3600MHz	
				25 dB at 3600~3800MHz	
				25 dB at 3800~4000MHz	
				20 dB at 4000~4400MHz	
				16 dB at 7000~7400MHz	
				16 dB at 7400~9750MHz	
				20 dB at 9750~10300MHz	
				16 dB at 10300~12750MHz	
SLFB18-5R500G-39TF	5425	4900~5950	1	35 dB at 30~2700MHz	0.55±0.10
				33 dB at 3400~3800MHz	
				9 dB at 6900~7000MHz	
				15 dB at 7200~7500MHz	
				20 dB at 9800~11900MHz	

SLFB19 TYPE

Part Number	Center Frequency	Pass Band	Max. IL in PB (at 25°C)	Attenuation	Thickness
Units	MHz	MHz	dB	dB	MM
Symbol	f ₀	PB	IL	-	T
SLFB19-2R450G-03TF	2450	2400~2500	1	20 dB Min. at 50~960MHz	0.60±0.05
				30 dB Min. at 1560~1606MHz	
				15 dB Min. at 1710~1990MHz	
				10 dB Min. at 3600MHz	
				35 dB Min. at 4800~5000MHz	
				25 dB Min. at 7200~7500MHz	

SLFB21 TYPE

Part Number	Center Frequency	Pass Band	Max. IL in PB (at 25°C)	Attenuation	Thickness
Units	MHz	MHz	dB	dB	MM
Symbol	f ₀	PB	IL	-	T
SLFB21-2R450G-31TF	2450	2400~2500	1.2	15 dB Min. at 1600MHz	0.90±0.10
				25 dB Min. at 3200MHz	
				20 dB Min. at 4800~5000MHz	
SLFB21-2R450G-33TF	2450	2400~2500	1.9	35 dB Min. at 824~960MHz	
				30 dB Min. at 1545~1605MHz	
				30 dB Min. at 1770~1990MHz	
				30 dB Min. at 2170MHz	
				27 dB Min. at 4800~5000MHz	
				25 dB Min. at 7200~7500MHz	
SLFB21-3R600G-31TF	3600	3300~3900	1.5	32 dB Min. at 824~960MHz	
				24 dB Min. at 1710~1990MHz	
				21 dB Min. at 1990~2170MHz	

				28.5 dB Min. at 6900~8070MHz	
--	--	--	--	------------------------------	--

SPECIFICATIONS

SLFB21 TYPE

Part Number	Center Frequency	Pass Band	Max. IL in PB (at 25°C)	Attenuation	Thickness
Units	MHz	MHz	dB	dB	MM
Symbol	f ₀	PB	IL	-	T
SLFB21-3R600G-41TF	3600	3400~3800	1.3	37.5 dB Min. at 1~2170MHz	0.70±0.10
				27.5 dB Min. at 2170~2400MHz	
				27.5 dB Min. at 2400~2500MHz	
				9.5 dB Min. at 2500~2800MHz	
				4.5 dB Min. at 4400~4800MHz	
				25 dB Min. at 4800~4900MHz	
				25 dB Min. at 4900~5337MHz	
				25 dB Min. at 5337~5430MHz	
				25 dB Min. at 5430~6800MHz	
				34.5 dB Min. at 6800~7600MHz	
				30 dB Min. at 7600~9000MHz	
				25 dB Min. at 9000~11400MHz	
				20 dB Min. at 11400~15200MHz	
SLFB21-3R800G-17TF	3800	3300~4200	2	36 dB at 450~2200MHz	
				38 dB at 2300~2483MHz	
				33 dB at 2496~2690MHz	
				25 dB at 5150~5850MHz	
				25 dB at 6600~8400MHz	
				15 dB at 9900~12600MHz	
SLFB21-4R700G-19TF	4700	4400~5000	1.8	37 dB at 450~2200MHz	
				37 dB at 2300~2483MHz	
				33 dB at 2496~2690MHz	
				15 dB at 5490~5670MHz	
				18 dB at 5670~5950MHz	
				18 dB at 6200~8000MHz	
				20 dB at 8800~10000MHz	
				15 dB at 13200~15000MHz	

SLFB22 TYPE

Part Number	Center Frequency	Pass Band	Max. IL in PB (at 25°C)	Attenuation	Thickness
Units	MHz	MHz	dB	dB	MM
Symbol	f ₀	PB	IL	-	T
SLFB22-3R600G-31TF	3600	3186.4~4186.4	2	35 dB Min. at 500~1711MHz	1.0±0.10
				28 dB Min. 33 dB typ. at 1711.84~2711.84MHz	
				28 dB Min. 33 dB at 4660.96~5660.96MHz	
				38 dB Min. at 5660~7610MHz	
				40 dB Min. 45 dB at 7610~8610MHz	
				20 dB Min. at 8610~11000MHz	
				15 dB Min. at 11000~14000MHz	
SLFB22-4R500G-31TF	4500	3823.68~5023.68	1.2	40 dB Min. at 500~874.56MHz	
				40 dB Min. at 6772.8~7972.8MHz	
				40 dB Min. at 7972.8~10921.92MHz	

				30 dB Min. at 10921.92~15000MHz	
--	--	--	--	------------------------------------	--

SPECIFICATIONS

SLFB22 TYPE

Part Number	Center Frequency	Pass Band	Max. IL in PB (at 25°C)	Attenuation	Thickness
Units	MHz	MHz	dB	dB	MM
Symbol	f_0	PB	IL	-	T
SLFB22-4R950G-31TF	4950	4415~5415	1.8	40 dB Min. at 500~3350MHz	1.0±0.10
				40 dB Min. at 6480~7500MHz	
				36 dB Min. at 6480~9250MHz	
				25 dB Min. at 9250~11200MHz	
				15 dB Min. at 11200~17200MHz	

SLFB32 TYPE

Part Number	Center Frequency	Pass Band	Max. IL in PB (at 25°C)	Attenuation	Thickness
Units	MHz	MHz	dB	dB	MM
Symbol	f_0	PB	IL	-	T
SLFB32-1R920G-31TF	1920	1680~2295	2.5	30 dB Min. @ DC~1400MHz	2.0±0.10
				30 dB Min. @ 2620~2705MHz	
				35 dB Min. @ 2705~2740MHz	
				35 dB Min. @ 2740~3115MHz	
				30 dB Min. @ 3115~3235MHz	
				30 dB Min. @ 3235~6590MHz	
				30 dB Min. @ 6590~7210MHz	
SLFB32-2R525G-11TF	2525	2150~2900	2.5	35 dB @ 259~650MHz	2.0±0.10
				28 dB @ 3208~3599MHz	
				35 dB @ 6157~6548MHz	
SLFB32-3R600G-12TF	3600	3160~4040	1.7dB Max. @3300~3900 MHz	30 dB Min. @ 824~960MHz	1.50±0.10
				24 dB Min. @ 1200~1990MHz	
			2dB Max. @3160~3300 MHz	36 dB Min. @ 2098~2598MHz	
				23 dB Min. @ 4600~5000MHz	
			2 dB Max. @3900~4040 MHz	43 dB Min. @ 5000~5600MHz	
				30 dB Min. @ 6349~6749MHz	
SLFB32-4R900G-31TF	4900	4700~5100	3	28 dB Min. @ 6900~8070MHz	1.50±0.10
				45 dB Min. @ 10~2000MHz	
				30 dB Min. @ 2000~3400MHz	
				30 dB Min. @ 3400~3800MHz	
				24 dB Min. @ 3800~4330MHz	
				25 dB Min. @ 4700~5100MHz	