APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO 60 °C △2	STORAGE TEMPERATURE RANGE	1 -25 °C TO 60 °C △2
	VOLTAGE		CURENT	

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△	2	DIS-E-00002227	TS. ITO	TU. TANIGUCHI	20190418

REMARK

1 PACKING MATERIAL IS NOT INCLUDED.

Unless otherwise specified, refer to JIS C 5402.

APPROVED	HO. MIWA	20050105
CHECKED	TH. KAMEYA	20050105
DESIGNED	SS. SATOH	20050105
DRAWN	SS. SATOH	20050105

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-121484-01

HRS	SPECIFICATION SHEET	PART NO.	TM21P-88P(**)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	△2	1/1

FORM HD0011-2-1

Sep.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.