

Sep.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE






NOTE 1. ( ) INDICATES THE REFERENCE DIMENSIONS.
2 COLORS ARE SHOWN IN TABLE-1.
3. PER PACK: 50 PIECES.

2 TABLE-1


	PART No.	HRS No.	COLOR
	TM21P-88P(11)	CL222-2862-9-11	LIGHT BEIGE
	TM21P-88P(12)	CL222-2862-9-12	MEDIUM GRAY
	TM21P-88P(13)	CL222-2862-9-13	BLACK
	TM21P-88P(14)	CL222-2862-9-14	NATURAL LIGHT GRAY
	TM21P-88P(15)	CL222-2862-9-15	RED
	TM21P-88P(16)	CL222-2862-9-16	GREEN
	TM21P-88P(17)	CL222-2862-9-17	BLUE
	TM21P-88P(18)	CL222-2862-9-18	YELLOW
	TM21P-88P(19)	CL222-2862-9-19	ORANGE
2	TM21P-88P(32)	CL222-2862-9-32	WHITE
2	TM21P-88P(33)	CL222-2862-9-33	VIOLET
2	TM21P-88P(34)	CL222-2862-9-34	PINK

ATTACHED HOOD CLOSED




HOOD ATTACHMENT PROCEDURE (FREE)

1. FIT THE OPENED HOOD ON THE CABLE AND CLOSE. HOOD DIRECTION IS SHOWN AS AN EXAMPLE.



2. SLIDE THE CLOSED HOOD TO THE PLUG LOCK POSITION UNTIL BEING LOCKED AT A.



NO.	MATERIAL	FINISH , REMARKS
1	POLYAMIDE	(2) UL94V-2 1

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	2	3	DIS-E-001276	TS. ITO	HO. MIWA	07. 02. 14

HRS HIROSE ELECTRIC CO., LTD.

APPROVED	HO. MIWA	05. 01. 05
CHECED	TH. KAMEYA	05. 01. 05
DESIGNED	SS. SATOH	05. 01. 05
DRAWN	SS. SATOH	05. 01. 05

DRAWING NO. EDC3-121484-01
PART NO. TM21P-88P(**)
CODE NO. 2 1/1