

GAR VFT69383X2NJN

3-Port Vehicular MIMO Antenna 698-960/1690-3800 MHz

The Gar VFT69383x2NJN multiport/multiband antenna provides an excellent solution for public safety, transportation, and aftermarket fleet applications. Configured for two-port operation over the 3G/4G/5G/ISM/CBRS bands and an additional port providing an active antenna for enabling GNSS global navigation services.

FEATURES AND BENEFITS

- One single-hole mount/fixing- reduces vehicle damage and the cost of installation
- Attractive IP67 low profile aerodynamic housing
- Multiband/Multiport operation LTE/GNSS navigation
- Operates well on a ground plane and without a ground plane

APPLICATIONS

- FirstNet/Public safety
- Transportation
- Aftermarket fleet
- 5G-ready
- Rugged LTE gateways
- Others

ELECTRICAL SPECIFICATIONS

Antenna Model	VFT69383x2NJN								
Number of Ports	3								
Port Configuration	2X – 3G/4G/5G/ISM/CBRS (LTE/CELL)								
Operating Frequency (MHz)	698-806	824-894	880-960	1690-1880	1850-1990	1910-2180	2300-2500	2500-2700	3300-3800
Avg. Peak Gain* (dBi) – Gnd. Plane [No Gnd. Plane]	0.7 [1.1]	0.5 [1.6]	0.2 [2.1]	3.7 [1.2]	3.0 [1.3]	2.5 [1.2]	3.7 [1.2]	4.6 [1.5]	5.5 [2.2]
Max Peak Gain* (dBi) – Gnd. Plane [No Gnd. Plane]	2.0 [2.1]	1.3 [3.2]	2.2 [3.7]	4.7 [1.1]	3.6 [1.6]	3.4 [1.6]	5.1 [1.6]	5.1 [2.4]	7.5 [3.8]
VSWR** – Avg, Gnd. Plane [No Gnd. Plane]	1.8 [1.9]	1.8 [1.8]	1.4 [1.7]	1.6 [1.7]	1.6 [1.5]	1.5 [1.5]	1.4 [1.6]	1.4 [1.5]	1.5 [1.3]
VSWR** – Max, Gnd. Plane [No Gnd. Plane]	2.5 [2.5]	2.2 [2.5]	2.2 [2.5]	2.0 [2.1]	2.0 [2.1]	2.2 [2.1]	2.1 [2.1]	2.0 [2.1]	2.0 [2.1]
Isolation** (dB)– Gnd. Plane [No Gnd. Plane]									
LTE1 to LTE2	-10 [-12]	-12 [-14]	-14 [-14]	-17 [-16]	-18 [-16]	-18 [-16]	-22 [-22]	-21 [-23]	-25 [-26]
LTE1 to GNSS	-41 [-40]	-45 [-42]	-45 [-42]	-41 [-39]	-49 [-45]	-50 [-48]	-60 [-55]	-56 [-53]	-47 [-45]
LTE2 to GNSS	-42 [-39]	-38 [-38]	-38 [-37]	-44 [-42]	-49 [-46]	-49 [-45]	-41 [-38]	-55 [-50]	-44 [-40]

ELECTRICAL SPECIFICATIONS	
Azimuth Plane 3 dB Beamwidth	360°, Omnidirectional
Nominal Impedance (Ohms)	50
Polarization	Linear Vertical
Max Power - Ambient 25°C (W)	30 (LTE/CELL)

Notes: (*) – This parameter is based on a 30cm (1ft) cable length. For the ground plane measurement, a 30cm (1ft) ground plane was used
(**) – This parameter is based on a 518cm (17ft) cable length. For the ground plane measurement, a 30cm (1ft) ground plane was used. Antenna specifications are subject to change according to the ground plane size.

MECHANICAL SPECIFICATIONS	
Dimensions – L x W x H – mm (inches)	179 x 63 x 48 (7.04 x 2.48 x 1.69)
Weight – kg (lbs.)	0.74 kg (1.6 lbs)
Cable Type	LMR 100- pigtails, LMR 195- jumper cables
Mounting	P-Mount
Color	Black or White
Radome Material	PC, UL94-V0
Baseplate Material	Aluminum

ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Outdoor Vehicle
Operating Temperature – °C (°F)	-30 to +70°C (-22 to +158°F)
Storage Temperature – °C (°F)	-40 to +85°C (-40 to +185°F)
Ingress Protection Rating	IP67
Rail Compliance Standards	EN61373 (shock and vibration), EN50155 (temperature)
Material Substance Compliance	RoHS

CONFIGURATION


PART NUMBER	CABLE LENGTH		CONNECTORS		COLOR
	PIGTAIL	JUMPER	LTE/CELL	GNSS	
VFT69383B2NJN-518Q	0.3 m (1 ft.)	4.9 m (16 ft)	SMA-male	SMA-male	Black
VFT69383W2NJN-518Q	0.3 m (1 ft.)	4.9 m (16 ft)	SMA-male	SMA-male	White

GNSS ANTENNA SPECIFICATIONS					
Frequency of Operation (MHz)	1559 - 1606				
Band	BEIDOU	GPS	GLONASS		
Frequency Band (MHz)	1561.098 ±2.046	1575.42 ±1.023	1602 ±5		
Absolute Gain (dBi) – Gnd. Plane [No Gnd. Plane]	3.4 [3.5]	4.9 [5.1]	5.4 [4.7]		
LNA Gain, Typ. @ room temp. (dBi)	28 ±3				
Noise Figure @ room temp., Max (dB)	≤ 2.5 @ 1575 MHz				
Max VSWR @ room temp.	≤ 2.0				
Polarization	RHCP				
Nominal Impedance (Ohms)	50				
DC Voltage (Vdc)	3.3				
Operating Supply Voltage (Vdc)	2.5 - 7.0				
Current Consumption, Max @ room temp mA)	8.5 ± 3 @ 3.0V				
Out-of-band Signal Rejection Min @ room temp (dBc)	80 @ 698-960 MHz	80 @ 1428-1511 MHz	50 @ 1627-1638 MHz	80 @ 1710-2700 MHz	70 @4900-5800 MHz
Input Max Power (dBm)	-10				
Cable Type	RG174, Black				

PACKAGING INFORMATION

PACKAGED DIMENSIONS	CARTON	MASTER CARTON	AIR PALLET	OCEAN PALLET
Number of Antennas	1	4	140	196
Height – mm (in.)	130 (5.12)	235 (9.25)	1335 (52.56)	1813 (71.38)
Length – mm (in.)	222 (8.74)	543 (21.38)	1200 (47.24)	1200 (47.24)
Width – mm (in.)	222 (8.74)	232 (9.13)	800 (31.5)	800 (31.5)
Shipping Weight – kg (lb.)	0.97(2.1)	4.41 (9.72)	167 (368)	229 (504)


MECHANICAL DRAWINGS





The Gar antenna can create an IP67 water-tight seal when installed on vehicles. Certain vehicles such as a Ford Explorer Interceptor have more narrow roof ridges that are tightly spaced together. For this type, vehicle special adapters are available.
See parts BKIT-VFX69383-001 (between ridges installation) and BKIT-VFX69383-003 (atop ridge installation) for product details.

RADIATION PATTERNS WITH GROUND PLANE - LTE ANTENNAS


698 MHz










725 MHz









880 MHz









RADIATION PATTERNS WITH GROUND PLANE - LTE ANTENNAS


960 MHz



1690 MHz





1920 MHz




RADIATION PATTERNS WITH GROUND PLANE - LTE ANTENNAS


2110 MHz










2400 MHz









2700 MHz










RADIATION PATTERNS WITH GROUND PLANE - LTE ANTENNAS


3400 MHz









3800 MHz










RADIATION PATTERNS WITHOUT GROUND PLANE - LTE ANTENNAS

698 MHz










RADIATION PATTERNS WITHOUT GROUND PLANE - LTE ANTENNAS


725 MHz










880 MHz









960 MHz










RADIATION PATTERNS WITHOUT GROUND PLANE - LTE ANTENNAS


1690 MHz










1920 MHz









2110 MHz









RADIATION PATTERNS WITHOUT GROUND PLANE - LTE ANTENNAS


2400 MHz



2700 MHz




3400 MHz



RADIATION PATTERNS WITHOUT GROUND PLANE - LTE ANTENNAS

3800 MHz



TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use.
TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

©2021 TE Connectivity. All Rights Reserved.

11/21 Original