1000 Eaton Boulevard
Cleveland, OH 44122
United States

# 2-Port Manual VGA/SVGA Video Switch (3x HD15F)

MODEL NUMBER: **B112-002-R**






### Highlights

- 2-port HD15 VGA/SVGA Push-Button Switch
- Rugged Metal Case

### System Requirements

- Computer with an HD15 port
- VGA or SVGA monitor with HD15M cable

### Package Includes

- B112-002-R Manual VGA/SVGA 2 Position Switch

### Description

Tripp Lite's 2-Port Manual VGA/SVGA Switch is the optimal solution for connecting two computers to one monitor or two monitors to one computer. The 2-Port Manual VGA/SVGA Switch features a fully-shielded rugged metal case with front-panel push-button switching. Interior printed circuit board design allows for crystal clear resolutions up to 1600x1280. It does not require any AC power to operate.

### Features

- Connects two computers to one monitor or two monitors to one computer
- Fully-shielded rugged metal case with front-panel push button switch
- Does not require external power, software, or complicated set-up procedures

## Specifications

| | |
|---|---|
| **OVERVIEW** | |
| UPC Code | 037332014269 |
| Technology | VGA/SVGA |
| **VIDEO** | |
| Max Supported Video Resolution | 1920 x 1080 @60Hz |
| **INPUT** | |
| Bus Powered | Yes |
| Product Length (in.) | 4.41 |
| Product Length (ft.) | 0.37 |

1000 Eaton Boulevard
Cleveland, OH 44122
United States

| | |
|---|---|
| **POWER** | |
| Power Consumption (Watts) | 0.5 |
| **PHYSICAL** | |
| Color | Silver |
| Material of Construction | Aluminum |
| Shipping Dimensions (hwd / in.) | 4.53 x 1.06 x 3.27 |
| Shipping Dimensions (hwd / cm) | 11.51 x 2.69 x 8.31 |
| Shipping Weight (lbs.) | 3.53 |
| Shipping Weight (kg) | 1.60 |
| Unit Dimensions (hwd / in.) | 0.940 x 4.400 x 2.700 |
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 0.33 |
| Unit Weight (kg) | 0.15 |
| **ENVIRONMENTAL** | |
| Operating Temperature Range | 14 to 131 °F (-10 to 55 °C) |
| Storage Temperature Range | 5 to 131 °F (-15 to 55 °C) |
| Relative Humidity | 5% to 90% RH, Non-Condensing |
| BTUs | 1.7 BTU/Hr |
| **COMMUNICATIONS** | |
| EDID Compatible | Yes |
| **CONNECTIONS** | |
| Number of Ports | 2 |
| Side A - Connector 1 | (2) HD15 (FEMALE) |
| Side B - Connector 1 | HD15 (FEMALE) |
| Connector Plating | Nickel |
| **FEATURES & SPECIFICATIONS** | |
| Port Selection | Pushbutton |
| Driver Required | No |
| **STANDARDS & COMPLIANCE** | |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) |

1000 Eaton Boulevard
Cleveland, OH 44122
United States

| WARRANTY & SUPPORT | |
|---|---|
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2022 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks are the property of their respective owners.