SIEMENS

Data sheet 6AV7863-4AB10-0AA0

SIMATIC IFP2200 Flat Panel 22" display (16: 9), without touch, only display, Extended version up to 30 m, 1920x 1080 pixels, for 24 V DC and 100-240 V AC, display port/DVI interface incl. DVI/USB cable 1.8 m



Figure similar

General information	
Product type designation	IFP2200
Short designation	Flat Panel 22" display ext.
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	21.5 in; 22"
Screen diagonal [cm]	56 cm
Display width	476 mm
Display height	268 mm
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216; 24 bit
Resolution (pixels)	
● Image resolution	1 920 x 1 080
● Horizontal image resolution	1 920 pixel
● Vertical image resolution	1 080 pixel
● Pixel size, horizontal	0.2475 mm
● Pixel size, vertical	0.2475 mm
General features	
● Brightness/contrast	250 cd/m² / 1 000:1
● non-reflective and tempered mineral glass screen	Yes
● Detachable from computer unit	30 m
● Luminance	250 cd/m²
Backlighting	
● Type of backlighting	LED
● MTBF backlighting (at 25 °C)	50 000 h; At 25°C
● Backlight dimmable	Yes; 0-100 %
Control elements	
Control elements	none
Input device	
● Integrated mouse cursor control	No
Keyboard fonts	
● Function keys	No
— Number of function keys	0
Touch operation	
● Design as touch screen	No
Installation type/mounting	

Subject to change without notice
© Copyright Siemens

Design	Built-in unit
Front mounting	Yes
Built-in unit	Yes
maximum permitted forward tilt angle from vertical	35°
maximum permitted backward tilt angle from vertical	35°
Supply voltage	
Type of supply voltage	AC/DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Rated value (AC)	100 V
permissible range, lower limit (AC)	90 V
permissible range, upper limit (AC)	264 V
Power loss	
Power loss, typ.	40 W
Power loss, max.	65 W
Interfaces	
USB on the rear	Yes
Connection for keyboard/mouse	USB
Video interfaces	
● analog video signal (VGA)	No
● DVI-D	Yes
● DisplayPort	Yes
Touch interfaces	
● USB	No
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes; Corresponds to UL 508
RCM (formerly C-TICK)	Yes
KC approval	Yes
Use in hazardous areas	
● FM Class I Division 2	No
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	45 °C; Vertical installation (horizontal)
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Relative humidity	
● Operation, max.	95 %; no condensation
Vibrations	
● Vibration load in operation	10 m/s²
● Vibration load during transport/storage	10 m/s²
Shock testing	
● Shock load during operation	150 m/s²
● shock acceleration during storage/transport	150 m/s²
Mechanics/material	
Enclosure material (front)	
● Aluminum	Yes
Dimensions	
Width of the housing front	560 mm
Height of housing front	380 mm
Mounting cutout, width	542 mm; Tolerance: +1 mm
Mounting cutout, height	362 mm; Tolerance: +1 mm
Overall depth	62.5 mm
Weights	

Subject to change without notice
© Copyright Siemens

Weight without packaging	6.5 kg
Weight incl. packaging	7.6 kg

last modified: 6/12/2020

Subject to change without notice
© Copyright Siemens