SIEMENS

Data sheet 3UG4583-1CW30



Insulation monitoring relay for ungrounded (IT) supply systems up to 400 V AC, 15-400 Hz and up to 600 V DC Measuring range 1-100 / 2-200 kohm Supply voltage 24-240 V AC/DC Width 45 mm 1 + 1 or 2 change-over contacts screw terminal

product brand name	SIRIUS
product designation	Insulation monitoring relay with analog setting
product type designation	3UG4
General technical data	
product function	Insulation monitor
type of voltage	
● for monitoring	AC/DC
● of the operating voltage for actuation	AC/DC
● of the control supply voltage	AC/DC
surge voltage resistance rated value	4 000 V
protection class IP	IP20
thermal current of the switching element with contacts maximum	4 A
reference code acc. to IEC 81346-2	K
Product Function	
product function error memory	Yes
Control circuit/ Control	
control supply voltage at AC	
● at 50 Hz rated value	24 ... 240 V
● at 60 Hz rated value	24 ... 240 V
control supply voltage at DC rated value	24 ... 240 V
operating range factor control supply voltage rated value at DC	
● initial value	0.85
● full-scale value	1.1
operating range factor control supply voltage rated value at AC at 50 Hz	
● initial value	0.85
● full-scale value	1.1
operating range factor control supply voltage rated value at AC at 60 Hz	
● initial value	0.85
● full-scale value	1.1
Measuring circuit	
measurable line frequency	15 ... 400 Hz
Auxiliary circuit	
number of NC contacts for auxiliary contacts	0
number of NC contacts delayed switching	0

Subject to change without notice
© Copyright Siemens

number of NO contacts for auxiliary contacts	0
number of NO contacts delayed switching	0
number of CO contacts	
● delayed switching	2
Main circuit	
operating frequency rated value	15 ... 400 Hz
Connections/ Terminals	
product function removable terminal for auxiliary and control circuit	No
type of electrical connection	screw-type terminals
type of connectable conductor cross-sections	
● solid	2x (0.75 ... 2.5 mm²)
● finely stranded with core end processing	2x (0.75 ... 2.5 mm²)
● connectable conductor cross-section solid	0.75 ... 2.5 mm²
● connectable conductor cross-section finely stranded with core end processing	0.75 ... 2.5 mm²
● AWG number as coded connectable conductor cross section solid	20 ... 12
● AWG number as coded connectable conductor cross section stranded	18 ... 14
● tightening torque with screw-type terminals	0.6 ... 0.8 N·m
Installation/ mounting/ dimensions	
mounting position	any
fastening method	snap-on fastening on 35 mm standard rail
height	78 mm
width	45 mm
depth	100 mm
required spacing	
● with side-by-side mounting	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
● for grounded parts	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— at the side	0 mm
— downwards	0 mm
● for live parts	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
Ambient conditions	
● ambient temperature during operation	-25 ... +60 °C
Certificates/ approvals	


General Product Approval	EMC	Declaration of Conformity	Test Certificates
CCC UL RCM EG-Konf.	Miscellaneous		Special Test Certificate


Subject to change without notice
© Copyright Siemens

Marine / Shipping	other	Railway
	Confirmation	Vibration and Shock


Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UG4583-1CW30
Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UG4583-1CW30
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3UG4583-1CW30
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UG4583-1CW30&lang=en
Characteristic: Derating
https://support.industry.siemens.com/cs/ww/en/ps/3UG4583-1CW30/manual






Subject to change without notice
© Copyright Siemens



Subject to change without notice
© Copyright Siemens



last modified: 12/23/2020

Subject to change without notice
© Copyright Siemens