

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICABLE STANDARD			
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO 85 °C(NOTE 1)	STORAGE TEMPERATURE RANGE
	VOLTAGE		APPLICABLE CONNECTORS
	CURRENT		OPERATING HUMIDITY RANGE
		-10 °C To + 60 °C	
		UL1007, AWG24	

SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	×	×
MARKING	CONFIRMED VISUALLY.		×	×

REMARKS		DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT		Y.NAGASHIMA	Y. Inoue	Miyazaki	K. Katayama	
Unless otherwise specified, refer to MIL-STD-1344.		'00.11.10	'00.11.10	'00.11.13	'00.11.14	
Note QT: Qualification Test AT: Assurance Test ×:Applicable Test						
HRS HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET		PART NO.		
CODE NO.(OLD)		DRAWING NO.	PEART NO		1/1	
CL		ELC4-162341	CL 5 4 1			