


Table.1 Stacking height and connector combinations 1

Board distance (Stacking height)	Header connector of Board α	Interposer	Header connector of Board β	Recommended spacer height(L)
8mm	FX10A-144P-SV(**)	FX10-144IP-44Q-8H(O3)	FX10A-144P-SV(**)	8±0.127mm
9mm	FX10A-144P-SV1(**)		FX10A-144P-SV(**)	9±0.127mm
10mm	FX10A-144P-SV1(**)		FX10A-144P-SV1(**)	10±0.127mm

Table.2 Pin configuration of Interposer  4[illegible]

S: Signal for Differential SE: Signal for Single-ended G1: Common ground 1 G2: Common ground 2

Note.

- ① The header connectors are decided by board distance (stacking height). Connector combination is shown in Table 1.
- ② Fixed side (Black side) of interposer should be mated with header mounted on board α .
Mating side (Gray side) should be mated with header mounted on board β .
- ③ Spacers are required to support the PWB's and protect the SMT solder joints.
Recommended spacer height is shown in Table 1.
- ④ Pin configuration is shown in Table 2.
This product consists of 44 Differential pairs, 8 Single-ended lines and 48 ground lines.
- ⑤ Lot No. shall be marked on the indicated position.
- ⑥ 50pcs of this product are packed in soft tray. See Fig.3 for details.





Fig.2 Mating cross section (Free)

3	Copper Alloy	Ni1.5μm+Au0.76μm	6	PS	(Tray)			
2	LCP(Black)	UL94V-0	5	Copper Alloy	Ni1μm			
1	LCP(Gray)	UL94V-0	4	Copper Alloy	Ni1μm 			
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1	 COUNT 9	DESCRIPTION OF REVISIONS DIS-F-00002513		DESIGNED AS. MATSUZAWA	CHECKED MK. EZAKI	DATE 17. 07. 14
 HIROSE ELECTRIC CO., LTD.	APPROVED		•MK. EZAKI		16. 03. 25		DRAWING NO. EDC-354344-03-03	
	CHECKED		•MK. EZAKI		16. 03. 25		PART NO. FX10-144IP-44Q-8H(C03)	
	DESIGNED		•MK. NAGATA		16. 03. 25		CODE NO. CL608-0008-2-03	
	DRAWN		•MK. NAGATA		16. 03. 25		 	

Oct.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




Fig.3 Drawing for packing (1:2) 6




Fig.4 Stacked tray drawing (1:2)

HRS	DRAWING NO.	EDC-354344-03-03		
	PART NO.	FX10-144IP-44Q-8H<03>		
	CODE NO.	CL608-0008-2-03	2	2