

Oct.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.






NOTE 1 LEAD CO-PLANARITY OF THIS PRODUCT TO BE 0.1MAX.
2 AREA OF INNER SMT LAND REQUIRES PATTERN PROHIBITION OR RESIST TREATMENT TO PREVENT THE PATTERN TOUCHING TO THE CONTACTS.
3 ( ) INDICATES A REFERENCE DIMENSION.
4 MANUFACTURING PROCESS COULD LEAVE SCRATCH AND/OR PUNCH MARKS HAVING NO AFFECT ON THE PRODUCT PERFORMANCE.
5 PACKAGING FOR THIS PRODUCT APPLIES EMBOSSED CARRIER TAPE PACKAGING.

HRS DRAWING FOR REFERENCE

RECOMMENDED LAND PATTERN DIMENSION
(METAL MASK THICKNESS:t=0.12)



NO.	MATERIAL	FINISH , REMARKS
2	BRASS 1	OVER PLATING:TIN PLATING 1μm min
		UNDER PLATING:NICKEL 2μm min 2
1	PA	BLACK, UL94V-0

NO.	MATERIAL	FINISH , REMARKS
5	PE	(COVER TAPE)
4	PS	(EMBOSSED CARRIER TAPE)
3	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm min
		LEAD AREA:GOLD 0.03μm min
		UNDER PLATING:NICKEL 1μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	2	1	DIS-F-006350	CR. TAKESHIMA	HT. YAMAGUCHI	12.08.24

HIROSE ELECTRIC CO., LTD.


APPROVED	HS. OKAWA	11.11.02
CHECKED	HT. YAMAGUCHI	11.11.02
DESIGNED	YJ. ASAO	11.11.02
DRAWN	CR. TAKESHIMA	11.11.02

DRAWING NO.	EDC3-330633-01
PART NO.	FX16M2-51S-0.5SH(30)
CODE NO.	CL575-3004-1-30

2 1/2


Oct.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


DRAWING FOR PACKING (2:1)



HRS DRAWING FOR REFERENCE

REELED DIMENSION (FREE)





DRAWING NO.	EDC3-330633-01
PART NO.	FX16M2-51S-0.5SH(30)
CODE NO.	CL575-3004-1-30

2/2

FORM HC0011-5-8