



- NOTE 1 HRS MARK SHOULD BE OPTIONAL.
2. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
 3. FOR MODIFICATION, ETC., PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
 4. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

1	PPS	LIGHT BROWN (UL94V-0)		2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm min.			
						LEAD AREA:TIN-PLATING 1μm min.			
						UNDER PLATING:NICKEL 1μm min.			
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS			
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA		07.01.12	DRAWING NO.		EDC3-071644-21		
		CHECED : HS. OZAWA		07.01.12	PART NO.		FX6A-50P-0.8SV2(71)		
		DESIGNED : KT. DOI		07.01.12	CODE NO.		CL576-0244-5-71		
		DRAWN : TS. MIYAKI		07.01.11					