SIEMENS

## Data sheet 3SU1050-4BL11-0AA0-Z X90



RONIS key-operated switch, 22 mm, round, metal, shiny, lock number SB30, with 2 keys, 3 switch positions I-O-II, latching, actuating angle 2x45°, 10:30h/12h/13:30h, Key removal I+O+II, possible special locks: SB31, 421, 455, Z=50-unit packaging


| | |
|---|---|
| **product brand name** | SIRIUS ACT |
| **product designation** | Key-operated switches |
| **design of the product** | Actuating/signaling element |
| **product type designation** | 3SU1 |
| **product line** | Metal, shiny, 22 mm |
| **manufacturer's article number of included key** | 3SU1950-0FB80-0AA0 |
| **Actuator** | |
| **principle of operation of the actuating element** | latching, 2x45° (10:30 h/12 h/13:30 h) |
| product extension optional light source | No |
| **color** | |
| ● of the actuating element | silver |
| **material of the actuating element** | metal |
| **shape of the actuating element** | Key |
| **outer diameter of the actuating element** | 29.5 mm |
| **number of switching positions** | 3 |
| **switch position for key distraction** | O+I+II |
| **actuating angle** | |
| ● clockwise | 45° |
| ● anticlockwise | 45° |
| **lock make** | RONIS |
| **key number** | SB30 |
| **Front ring** | |
| **product component front ring** | Yes |
| **design of the front ring** | Standard |
| **material of the front ring** | Metal, high gloss |
| **color of the front ring** | silver |
| **General technical data** | |
| **protection class IP** | IP66, IP67, IP69(IP69K) |
| ● of the terminal | IP20 |
| **degree of protection NEMA rating** | 1, 2, 3, 3R, 4, 4X, 12, 13 |
| **shock resistance** | |
| ● acc. to IEC 60068-2-27 | Sinusoidal half-wave 50g / 11 ms |
| **vibration resistance** | |
| ● acc. to IEC 60068-2-6 | 10 ... 500 Hz: 5g |
| **operating frequency maximum** | 1 800 1/h |
| mechanical service life (switching cycles) typical | 300 000 |
| **reference code acc. to IEC 81346-2** | S |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| **Ambient conditions** | |
| ● ambient temperature during operation | -25 ... +70 °C |
| ● ambient temperature during storage | -40 ... +80 °C |
| environmental category during operation acc. to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95 %) |
| **Installation/ mounting/ dimensions** | |
| **height** | 29.5 mm |
| **width** | 29.5 mm |
| **shape of the installation opening** | round |
| **mounting diameter** | 22.3 mm |
| **positive tolerance of installation diameter** | 0.4 mm |
| **mounting height** | 49.4 mm |
| **installation width** | 29.5 mm |
| **installation depth** | 25.4 mm |
| **Certificates/ approvals** | |
| **Further information** | |

**Information- and Downloadcenter (Catalogs, Brochures,…)**
https://www.siemens.com/ic10
**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-4BL11-0AA0-Z X90
**Cax online generator**
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-4BL11-0AA0-Z X90
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-4BL11-0AA0-Z X90
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-4BL11-0AA0-Z X90&lang=en


© Copyright Siemens




**last modified:** 2/1/2021


Subject to change without notice
© Copyright Siemens