



Figure similar

Duplex starter with alternator Size 0 Three phase full voltage Solid-state overload relay OLRelay amp range 3-12A 110VAC 50HZ / 120VAC 60HZ coil Combination type Two 30A disconnect switches Encl NEMA type 4 painted steel Water/dust tight weather proof

|                                                                         |                                                                            |
|-------------------------------------------------------------------------|----------------------------------------------------------------------------|
| product brand name                                                      | Class 84                                                                   |
| design of the product                                                   | Duplex controller with two non-fusible disconnect switches with alternator |
| special product feature                                                 | ESP200 overload relay                                                      |
| <b>General technical data</b>                                           |                                                                            |
| weight [lb]                                                             | 70 lb                                                                      |
| Height x Width x Depth [in]                                             | 34 × 25 × 8 in                                                             |
| touch protection against electrical shock                               | NA for enclosed products                                                   |
| installation altitude [ft] at height above sea level maximum            | 6560 ft                                                                    |
| ambient temperature [°F]                                                |                                                                            |
| • during storage                                                        | -22 ... +149 °F                                                            |
| • during operation                                                      | -4 ... +104 °F                                                             |
| ambient temperature                                                     |                                                                            |
| • during storage                                                        | -30 ... +65 °C                                                             |
| • during operation                                                      | -20 ... +40 °C                                                             |
| country of origin                                                       | USA                                                                        |
| <b>Horsepower ratings</b>                                               |                                                                            |
| yielded mechanical performance [hp] for 3-phase AC motor                |                                                                            |
| • at 200/208 V rated value                                              | 2 hp                                                                       |
| • at 220/230 V rated value                                              | 2 hp                                                                       |
| • at 460/480 V rated value                                              | 5 hp                                                                       |
| • at 575/600 V rated value                                              | 5 hp                                                                       |
| <b>Contactor</b>                                                        |                                                                            |
| size of contactor                                                       | NEMA controller size 0                                                     |
| number of NO contacts for main contacts                                 | 3                                                                          |
| operating voltage for main current circuit at AC at 60 Hz maximum       | 600 V                                                                      |
| operational current at AC at 600 V rated value                          | 18 A                                                                       |
| mechanical service life (switching cycles) of the main contacts typical | 10000000                                                                   |
| <b>Auxiliary contact</b>                                                |                                                                            |
| number of NC contacts at contactor for auxiliary contacts               | 0                                                                          |
| number of NO contacts at contactor for auxiliary contacts               | 1                                                                          |
| number of total auxiliary contacts maximum                              | 8                                                                          |
| contact rating of auxiliary contacts of contactor according to UL       | 10A@600VAC (A600), 5A@600VDC (P600)                                        |

| Coil                                                                                             |                                        |
|--------------------------------------------------------------------------------------------------|----------------------------------------|
| type of voltage of the control supply voltage                                                    | AC                                     |
| control supply voltage                                                                           |                                        |
| • at DC rated value                                                                              | 0 ... 0 V                              |
| • at AC at 50 Hz rated value                                                                     | 110 ... 110 V                          |
| • at AC at 60 Hz rated value                                                                     | 120 ... 120 V                          |
| holding power at AC minimum                                                                      | 8.6 W                                  |
| apparent pick-up power of magnet coil at AC                                                      | 218 V·A                                |
| apparent holding power of magnet coil at AC                                                      | 25 V·A                                 |
| operating range factor control supply voltage rated value of magnet coil                         | 0.85 ... 1.1                           |
| percental drop-out voltage of magnet coil related to the input voltage                           | 50 %                                   |
| switch ON delay time                                                                             | 19 ... 29 ms                           |
| OFF delay time                                                                                   | 10 ... 24 ms                           |
| Overload relay                                                                                   |                                        |
| product function                                                                                 |                                        |
| • overload protection                                                                            | Yes                                    |
| • phase failure detection                                                                        | Yes                                    |
| • asymmetry detection                                                                            | Yes                                    |
| • ground fault detection                                                                         | Yes                                    |
| • test function                                                                                  | Yes                                    |
| • external reset                                                                                 | Yes                                    |
| reset function                                                                                   | Manual, automatic and remote           |
| trip class                                                                                       | Class 5 / 10 / 20 (factory set) / 30   |
| adjustable current response value current of the current-dependent overload release              | 3 ... 12 A                             |
| tripping time at phase-loss maximum                                                              | 3 s                                    |
| relative repeat accuracy                                                                         | 1 %                                    |
| number of NC contacts of auxiliary contacts of overload relay                                    | 1                                      |
| number of NO contacts of auxiliary contacts of overload relay                                    | 1                                      |
| operational current of auxiliary contacts of overload relay                                      |                                        |
| • at AC at 600 V                                                                                 | 5 A                                    |
| • at DC at 250 V                                                                                 | 1 A                                    |
| contact rating of auxiliary contacts of overload relay according to UL                           | 5A@600VAC (B600), 1A@250VDC (R300)     |
| insulation voltage                                                                               |                                        |
| • with single-phase operation at AC rated value                                                  | 600 V                                  |
| • with multi-phase operation at AC rated value                                                   | 300 V                                  |
| Disconnect Switch                                                                                |                                        |
| response value of switch disconnecter                                                            | 30A / 600V                             |
| design of fuse holder                                                                            | non-fusible                            |
| operating class of the fuse link                                                                 | non-fusible                            |
| Enclosure                                                                                        |                                        |
| degree of protection NEMA rating of the enclosure                                                | NEMA Type 4                            |
| design of the housing                                                                            | Dust-tight, watertight & weather proof |
| Mounting/wiring                                                                                  |                                        |
| mounting position                                                                                | Vertical                               |
| fastening method                                                                                 | Surface mounting and installation      |
| type of electrical connection for supply voltage line-side                                       | Box lug                                |
| tightening torque [lbf·in] for supply                                                            | 35 ... 35 lbf·in                       |
| type of connectable conductor cross-sections at line-side at AWG cables single or multi-stranded | 1x (14 ... 2 AWG)                      |
| temperature of the conductor for supply maximum permissible                                      | 75 °C                                  |
| material of the conductor for supply                                                             | AL or CU                               |
| type of electrical connection for load-side outgoing feeder                                      | Screw-type terminals                   |
| tightening torque [lbf·in] for load-side outgoing feeder                                         | 20 ... 20 lbf·in                       |

|                                                                                                                              |                                                     |
|------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| type of connectable conductor cross-sections at AWG cables for load-side outgoing feeder single or multi-stranded            | 1x (14 ... 2 AWG)                                   |
| temperature of the conductor for load-side outgoing feeder maximum permissible                                               | 75 °C                                               |
| material of the conductor for load-side outgoing feeder                                                                      | AL or CU                                            |
| type of electrical connection of magnet coil                                                                                 | Screw-type terminals                                |
| tightening torque [lbf·in] at magnet coil                                                                                    | 5 ... 12 lbf·in                                     |
| type of connectable conductor cross-sections of magnet coil at AWG cables single or multi-stranded                           | 2x (16 ... 12 AWG)                                  |
| temperature of the conductor at magnet coil maximum permissible                                                              | 75 °C                                               |
| material of the conductor at magnet coil                                                                                     | CU                                                  |
| type of electrical connection at contactor for auxiliary contacts                                                            | Screw-type terminals                                |
| tightening torque [lbf·in] at contactor for auxiliary contacts                                                               | 10 ... 15 lbf·in                                    |
| type of connectable conductor cross-sections at contactor at AWG cables for auxiliary contacts single or multi-stranded      | 1x (12 AWG), 2x (16 ... 14 AWG), 2x (18 ... 16 AWG) |
| temperature of the conductor at contactor for auxiliary contacts maximum permissible                                         | 75 °C                                               |
| material of the conductor at contactor for auxiliary contacts                                                                | CU                                                  |
| type of electrical connection at overload relay for auxiliary contacts                                                       | Screw-type terminals                                |
| tightening torque [lbf·in] at overload relay for auxiliary contacts                                                          | 7 ... 10 lbf·in                                     |
| type of connectable conductor cross-sections at overload relay at AWG cables for auxiliary contacts single or multi-stranded | 2x (20 ... 14 AWG)                                  |
| temperature of the conductor at overload relay for auxiliary contacts maximum permissible                                    | 75 °C                                               |
| material of the conductor at overload relay for auxiliary contacts                                                           | CU                                                  |
| <b>Short-circuit current rating</b>                                                                                          |                                                     |
| design of the fuse link for short-circuit protection of the main circuit required                                            | 10kA@600V (Class H or K); 100kA@600V (Class R or J) |
| certificate of suitability                                                                                                   | NEMA ICS 2; UL 508; CSA 22.2, No.14                 |

#### Further information

##### Industrial Controls - Product Overview (Catalogs, Brochures,...)

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:84CUC92EDF>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<https://support.industry.siemens.com/cs/US/en/ps/US2:84CUC92EDF>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:84CUC92EDF&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:84CUC92EDF&lang=en)


##### Certificates/approvals

<https://support.industry.siemens.com/cs/US/en/ps/US2:84CUC92EDF/certificate>



# SCHEMATIC DIAGRAM

Class 83 & 84 Duplex W/Auto Alternation Size 0-4



last modified:

4/9/2020