NCS2300

Headset Detection Interface

The NCS2300 is a compact and cost effective headset detection interface IC. It integrates a comparator, OR gate, and N−channel MOSFET to detect the presence of a stereo headset with a microphone. Pull−up resistors for the detection pins are internalized. A built in resistor divider provides the reference voltage for detecting the left audio channel. The logic low output of the OR gate indicates the headset has been connected properly. The NCS2300 comes in a space saving UDFN6 package (1.2 x 1.0 mm).

Features

- Supply Voltage: 1.6 V to 2.75 V
- Low Quiescent Supply Current: 7.5 μA typical @ V_{DD} = 1.8 V
- Integrated Resistors, Comparator, OR Gate, and N−Channel MOSFET
- Space Saving UDFN6 Package
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant


Typical Applications

- Cell Phones, Smartphones
- Tablets
- Notebooks

ON Semiconductor®

http://onsemi.com

MARKING DIAGRAM




UDFN6
MU SUFFIX
CASE 517AA



A = Specific Device Code
M = Date Code
▪ = Pb−Free Package

PIN DIAGRAM



Top View

ORDERING INFORMATION

Device	Package	Shipping†
NCS2300MUTAG	UDFN6 (Pb−Free)	3000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2014




Figure 1. Typical Application Schematic




Figure 2. Block Diagram

Table 1. OUTPUT LOGIC

Inputs		Outputs		
L_detect	**GND_detect**	**OUT**	**MIC**	**Headset**
0	0	0	1 (external pull−up)	Detected
0	1	1	0	Not Detected
1	0	1	0	
1	1	1	0	

Table 2. PIN DESCRIPTION

Pin	Name	Type	Description
1	GND	Power	GND is connected to the system ground.
2	MIC	Output	The open drain MIC output controls the bias on the MIC line. When the headset is not present, MIC is pulled low. When the headset is present, MIC is pulled up to the MIC bias voltage through an external pull−up resistor.
3	GND_detect	Input	GND_detect is the OR gate input. An internal 1 MΩ pull−up resistor pulls this pin high when the headset is not present.
4	L_detect	Input	L_detect is the comparator input. An internal 1 MΩ pull−up resistor pulls this pin high when the headset is not present.
5	VDD	Power	VDD is connected to the system power supply. A 0.1 μF decoupling capacitor is recommended as close as possible to this pin.
6	OUT	Output	OUT is a logic output that indicates whether the headset has been properly connected. OUT will be logic low only when GND_detect and L_detect are low.

Table 3. ABSOLUTE MAXIMUM RATINGS (Note 1)

Rating	Symbol	Value	Unit
Supply Voltage Range	V_{DD}	0 to 2.75	V
L_detect Input Pin Voltage Range	V_{L_detect}	−0.1 to V_{DD} + 0.1	V
GND_detect Input Pin Voltage Range	V_{GND_detect}	−0.1 to V_{DD} + 0.1	
MIC Output Pin Voltage Range	V_{MIC}	0 to 6.0	V
Maximum MIC Current	I_{MIC}	2	mA
Maximum Junction Temperature	$T_{J(max)}$	+125	°C
Storage Temperature Range	T_{stg}	−65 to +150	°C
ESD Capability (Note 2) Human Body Model Machine Model	 ESD_{HBM} ESD_{MM}	 5000 250	V
Latch−up Current (Note 3)	I_{LU}	800	mA
Moisture Sensitivity Level (Note 4)	MSL	Level 1	

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to ELECTRICAL CHARACTERISTICS and APPLICATION INFORMATION for Safe Operating Area.
2. This device series incorporates ESD protection and is tested by the following methods:
   ESD Human Body Model tested per AEC−Q100−002 (JEDEC standard: JESD22−A114)
   ESD Machine Model tested per AEC−Q100−003 (JEDEC standard: JESD22−A115)
3. Latch−up Current tested per JEDEC standard: JESD78
4. Moisture Sensitivity Level tested per IPC/JEDEC standard: J − STD − 020A

Table 4. OPERATING RANGES

Rating	Conditions	Symbol	Min	Typ	Max	Unit
Power Supply Voltage		V_{DD}	1.6	1.8	2.75	V
Input Voltage	L_detect and GND_detect pins	V_{IN}	0		V_{DD}	V
Input Transition Rise or Fall Rate	GND_detect pin	$\Delta t / \Delta V$	0		10	ns/V
Bias Voltage on MIC Output		V_{MIC}	0		3.0	V
Ambient Temperature		T_A	−40		85	°C
Junction Temperature		T_J	−40		125	°C

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

Table 5. ELECTRICAL CHARACTERISTICS Typical values are referenced to T_A = 25°C, V_{DD} = 1.8 V, unless otherwise noted. Min/max values apply from T_A = −40°C to 85°C, unless otherwise noted. (Note 5)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
SUPPLY CHARACTERISTICS						
Quiescent Supply Current	V_{GND_detect} = 1.8 V or 0 V	I_{DD}		7.5	12	μA
INPUT CHARACTERISTICS OF L_DETECT						
Voltage Input Low	V_{DD} = 1.8 V	V_{IL}			1.33	V
Voltage Input High	V_{DD} = 1.8 V	V_{IH}	1.5			V
Propagation Delay to OUT	C_{out} = 15 pF, GND_detect = 0 V, L_detect = 1.31 V to 1.52 V	t_{pLH}, t_{pHL}		480		ns
Low Voltage Input Leakage	V_{L_detect} = 0 V	I_{IL}		1.8		μA
High Voltage Input Leakage	V_{L_detect} = 1.8 V	I_{IH}		500		pA
Input Capacitance	f = 1 MHz	C_{IN}		3		pF
INPUT CHARACTERISTICS OF GND_DETECT						
Voltage Input Low	V_{DD} = 1.8 V	V_{IL}			0.63	V
Voltage Input High	V_{DD} = 1.8 V	V_{IH}	1.17			V
Propagation Delay to OUT	C_{out} = 15 pF, R_L = 1 MΩ, L_detect = 0 V, GND_detect = 0 to 1.8 V	t_{pLH}, t_{pHL}		550		ps
Low Voltage Input Leakage	V_{GND_detect} = 0 V	I_{IL}		1.8		μA
High Voltage Input Leakage	V_{GND_detect} = 1.8 V	I_{IH}		500		pA
Input Capacitance	f = 1 MHz	C_{IN}		3		pF
OUTPUT CHARACTERISTICS OF OUT						
Voltage Output Low	V_{DD} = 1.8 V, I_{OH} = 0.1 mA	V_{OL}			0.10	V
Voltage Output High	V_{DD} = 1.8 V, I_{OH} = −0.1 mA	V_{OH}	1.70			V
Rise Time	C_{OUT} = 15 pF, R_L = 1 MΩ	t_{rise}		7		ns
Fall Time	C_{OUT} = 15 pF, R_L = 1 MΩ	t_{fall}		4		ns
CHARACTERISTICS OF MIC						
Drain−Source On Resistance of NMOS	V_{DD} = 1.8 V, I_{MIC} = 1 mA	$R_{DS(on)}$		0.9	1.4	Ω

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. Guaranteed by characterization and/or design.

TYPICAL CHARACTERISTICS




Figure 3. Supply Current vs. Temperature




Figure 4. V_{OH} vs. I_{OH} of OUT Pin




Figure 5. V_{OL} vs. I_{OL} of OUT Pin




Figure 6. On Resistance vs. Drain Current at V_{DD} = 1.6 V




Figure 7. On Resistance vs. Drain Current at V_{DD} = 1.8 V




Figure 8. On Resistance vs. Drain Current at V_{DD} = 2.0 V

TYPICAL CHARACTERISTICS




Figure 9. Low to High Propagation to OUT with Changing Input Overdrive of L_detect




Figure 10. High to Low Propagation to OUT with Changing Input Overdrive of L_detect

APPLICATIONS INFORMATION

SUPPLY VOLTAGE

The NCS2300 works with a wide range of supply voltages from 1.6 V to 2.75 V. A 0.1 μF decoupling capacitor should be placed as close as possible to the VDD pin. Since the NCS2300 has built in latch-up immunity up to 800 mA, series resistors are not recommended on VDD.

AUDIO JACK DETECTION

The NCS2300 is designed to simplify the detection of a stereo audio connector with a microphone contact. When the headset is not connected, the internal pull−up resistors on L_detect and GND_detect pull those pins high. When the headset is connected to the switched audio jack, the headset ground and left audio channel trigger L_detect and GND_detect to logic low.

The NCS2300 can work with either the CTIA or OMTP standard. In order to support both standards simultaneously, a cross point switch and additional circuitry is necessary to detect and swap the ground and microphone pins.

MIC PIN BIASING


The typical application schematic in Figure 1 shows the recommended 2.2 kΩ pull−up resistor to the MIC bias voltage. The MIC bias voltage can exceed VDD and can go as high as 3 V. While the headset is not detected, the internal NMOS transistor is enabled to mute the MIC signal. In the typical application scenario with a 2.2 kΩ pull−up to a 2.3 V MIC bias voltage, the MIC pin is pulled near 1 mV when the headset is not present. The internal NMOS transistor is optimized to sink up to 2 mA of current, allowing some flexibility in the selection of the pull−up resistor and MIC bias voltage.

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS


ON Semiconductor®


UDFN6, 1.2x1.0, 0.4P
CASE 517AA−01
ISSUE D

DATE 03 SEP 2010




SCALE 8:1







DETAIL A
Bottom View
(Optional)



DETAIL B
Side View
(Optional)





BOTTOM VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 mm FROM TERMINAL.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

	MILLIMETERS	
DIM	MIN	MAX
A	0.45	0.55
A1	0.00	0.05
A3	0.127 REF	
b	0.15	0.25
D	1.20 BSC	
E	1.00 BSC	
e	0.40 BSC	
L	0.30	0.40
L1	0.00	0.15
L2	0.40	0.50


GENERIC MARKING DIAGRAM*



X = Specific Device Code
M = Date Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

MOUNTING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON22068D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	6 PIN UDFN, 1.2X1.0, 0.4P	PAGE 1 OF 1

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT
North American Technical Support:
Voice Mail: 1 800−282−9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:
Phone: 00421 33 790 2910
For additional information, please contact your local Sales Representative

◊