



## Screw Terminal Blocks

### 230 K/ 3

terminal block, 3 pole, insulating material: PA, cross-section rating: 2.5 mm<sup>2</sup>, pin spacing: 8.00 mm, mounting hole diameter: 2.8 mm, fixing: screw, voltage rating: 450 V, current rating: 24 A



### Order Info

|                            |               |
|----------------------------|---------------|
| reference number (ref.no.) | 121603        |
| PU                         | 1,500         |
| EAN                        | 4028012105304 |

### Type

|                         |                     |
|-------------------------|---------------------|
| type                    | terminal block      |
| number of poles         | 3 pole              |
| clamping units per pole | 1                   |
| colour                  | natural             |
| cross-section rating    | 2.5 mm <sup>2</sup> |

### Technical Data

|                                    |                     |
|------------------------------------|---------------------|
| voltage rating                     | 450 V               |
| current rating                     | 24 A                |
| insulating material                | PA                  |
| contact material                   | brass               |
| core cross-section min.            | 0.5 mm <sup>2</sup> |
| core cross-section max.            | 4.0 mm <sup>2</sup> |
| flammability rating                | V-2                 |
| min. ambient temperature           | -40 °C              |
| max. ambient temperature operation | 85 °C               |
| type of conductor solid            | yes                 |
| type of conductor flexible         | yes                 |
| type of conductor stranded         | yes                 |
| stripping length                   | 5.0-5.5 mm          |
| mounting hole diameter             | 2.8 mm              |
| pin spacing                        | 8.00 mm             |
| fixing                             | screw               |

### Approvals

|                  |                              |
|------------------|------------------------------|
| acc. to EN 60998 | <a href="#">Download PDF</a> |
|------------------|------------------------------|

|                   |                              |
|-------------------|------------------------------|
| <b>acc. to UL</b> | <a href="#">Download PDF</a> |
|-------------------|------------------------------|

|                    |                              |
|--------------------|------------------------------|
| <b>acc. to CSA</b> | <a href="#">Download PDF</a> |
|--------------------|------------------------------|

## Accessories

|                  |        |
|------------------|--------|
| <b>230 BZ/ 3</b> | 191203 |
|------------------|--------|

|                |        |
|----------------|--------|
| <b>ZEL 110</b> | 196420 |
|----------------|--------|