



Screw Terminal Blocks

1000/ 2 DS

terminal block, 2 pole, insulating material: PA, cross-section rating: 6.0 mm², pin spacing: 12.00 mm, mounting hole diameter: 3.6 mm, wire protector (DS): yes, fixing: screw, voltage rating: 500 V, current rating: 41 A



Order Info

reference number (ref.no.)	125302
PU	1,000
EAN	4028012106172

Type

type	terminal block
number of poles	2 pole
clamping units per pole	1
colour	natural
cross-section rating	6.0 mm ²
wire protector (DS)	yes

Technical Data

voltage rating	500 V
current rating	41 A
insulating material	PA
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	6.0 mm ²
flammability rating	V-2
min. ambient temperature	-40 °C
max. ambient temperature operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.5-8.0 mm
mounting hole diameter	3.6 mm
pin spacing	12.00 mm
fixing	screw

Approvals

acc. to EN 60998	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

1000 BZ/ 2	191402
ABK 406/ 2	193302
ZEL 110	196420