



## Silicon PIN Photodiode



VBP104S



VBP104SR

### FEATURES

- Package type: surface mount
- Package form: GW, RGW
- Dimensions (L x W x H in mm): 6.4 x 3.9 x 1.2
- Radiant sensitive area (in mm<sup>2</sup>): 4.4
- High photo sensitivity
- High radiant sensitivity
- Suitable for visible and near infrared radiation
- Fast response times
- Angle of half sensitivity:  $\phi = \pm 65^\circ$
- Floor life: 168 h, MSL 3, acc. J-STD-020
- Lead (Pb)-free reflow soldering
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### DESCRIPTION

VBP104S and VBP104SR are high speed and high sensitive PIN photodiodes. It is a surface mount device (SMD) including the chip with a 4.4 mm<sup>2</sup> sensitive area detecting visible and near infrared radiation.

### APPLICATIONS

- High speed photo detector

### PRODUCT SUMMARY

| COMPONENT | $I_{ra}$ (μA) | $\phi$ (deg) | $\lambda_{0.1}$ (nm) |
|-----------|---------------|--------------|----------------------|
| VBP104S   | 35            | $\pm 65$     | 430 to 1100          |
| VBP104SR  | 35            | $\pm 65$     | 430 to 1100          |

#### Note

- Test conditions see table "Basic Characteristics"

### ORDERING INFORMATION

| ORDERING CODE | PACKAGING     | REMARKS                      | PACKAGE FORM     |
|---------------|---------------|------------------------------|------------------|
| VBP104S       | Tape and reel | MOQ: 1000 pcs, 1000 pcs/reel | Gullwing         |
| VBP104SR      | Tape and reel | MOQ: 1000 pcs, 1000 pcs/reel | Reverse gullwing |

#### Note

- MOQ: minimum order quantity

### ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25^\circ\text{C}$ , unless otherwise specified)

| PARAMETER                           | TEST CONDITION                    | SYMBOL     | VALUE         | UNIT             |
|-------------------------------------|-----------------------------------|------------|---------------|------------------|
| Reverse voltage                     |                                   | $V_R$      | 60            | V                |
| Power dissipation                   | $T_{amb} \leq 25^\circ\text{C}$   | $P_V$      | 215           | mW               |
| Junction temperature                |                                   | $T_j$      | 100           | $^\circ\text{C}$ |
| Operating temperature range         |                                   | $T_{amb}$  | - 40 to + 100 | $^\circ\text{C}$ |
| Storage temperature range           |                                   | $T_{stg}$  | - 40 to + 100 | $^\circ\text{C}$ |
| Soldering temperature               | Acc. reflow solder profile fig. 8 | $T_{sd}$   | 260           | $^\circ\text{C}$ |
| Thermal resistance junction/ambient |                                   | $R_{thJA}$ | 350           | K/W              |



| BASIC CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                               |                 |      |                     |      |                             |
|----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-----------------|------|---------------------|------|-----------------------------|
| PARAMETER                                                                                    | TEST CONDITION                                                                | SYMBOL          | MIN. | TYP.                | MAX. | UNIT                        |
| Forward voltage                                                                              | $I_F = 50\text{ mA}$                                                          | $V_F$           |      | 1                   | 1.3  | V                           |
| Breakdown voltage                                                                            | $I_R = 100\text{ }\mu\text{A}$ , $E = 0$                                      | $V_{(BR)}$      | 60   |                     |      | V                           |
| Reverse dark current                                                                         | $V_R = 10\text{ V}$ , $E = 0$                                                 | $I_{ro}$        |      | 2                   | 30   | nA                          |
| Diode capacitance                                                                            | $V_R = 0\text{ V}$ , $f = 1\text{ MHz}$ , $E = 0$                             | $C_D$           |      | 48                  |      | pF                          |
|                                                                                              | $V_R = 3\text{ V}$ , $f = 1\text{ MHz}$ , $E = 0$                             | $C_D$           |      | 17                  | 40   | pF                          |
| Open circuit voltage                                                                         | $E_e = 1\text{ mW/cm}^2$ , $\lambda = 950\text{ nm}$                          | $V_o$           |      | 350                 |      | mV                          |
| Temperature coefficient of $V_o$                                                             | $E_e = 1\text{ mW/cm}^2$ , $\lambda = 950\text{ nm}$                          | $TK_{V_o}$      |      | - 2.6               |      | mV/K                        |
| Short circuit current                                                                        | $E_e = 1\text{ mW/cm}^2$ , $\lambda = 950\text{ nm}$                          | $I_k$           |      | 32                  |      | $\mu\text{A}$               |
| Temperature coefficient of $I_k$                                                             | $E_e = 1\text{ mW/cm}^2$ , $\lambda = 950\text{ nm}$                          | $TK_{I_k}$      |      | 0.1                 |      | %/K                         |
| Reverse light current                                                                        | $E_e = 1\text{ mW/cm}^2$ , $\lambda = 950\text{ nm}$ ,<br>$V_R = 5\text{ V}$  | $I_{ra}$        | 25   | 35                  |      | $\mu\text{A}$               |
| Angle of half sensitivity                                                                    |                                                                               | $\phi$          |      | $\pm 65$            |      | deg                         |
| Wavelength of peak sensitivity                                                               |                                                                               | $\lambda_p$     |      | 940                 |      | nm                          |
| Range of spectral bandwidth                                                                  |                                                                               | $\lambda_{0.1}$ |      | 430 to 1100         |      | nm                          |
| Noise equivalent power                                                                       | $V_R = 10\text{ V}$ , $\lambda = 950\text{ nm}$                               | NEP             |      | $4 \times 10^{-14}$ |      | $\text{W}/\sqrt{\text{Hz}}$ |
| Rise time                                                                                    | $V_R = 10\text{ V}$ , $R_L = 1\text{ k}\Omega$ ,<br>$\lambda = 820\text{ nm}$ | $t_r$           |      | 100                 |      | ns                          |
| Fall time                                                                                    | $V_R = 10\text{ V}$ , $R_L = 1\text{ k}\Omega$ ,<br>$\lambda = 820\text{ nm}$ | $t_f$           |      | 100                 |      | ns                          |

#### BASIC CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 1 - Reverse Dark Current vs. Ambient Temperature




Fig. 2 - Relative Reverse Light Current vs. Ambient Temperature




Fig. 3 - Reverse Light Current vs. Irradiance




Fig. 6 - Relative Spectral Sensitivity vs. Wavelength




Fig. 4 - Reverse Light Current vs. Reverse Voltage




Fig. 7 - Relative Radiant Sensitivity vs. Angular Displacement





Fig. 5 - Diode Capacitance vs. Reverse Voltage



## PACKAGE DIMENSIONS FOR VBP104S in millimeters




Drawing-No.: 6.541-5088.01-4

Issue: 1; 15.04.10

22107



## PACKAGE DIMENSIONS FOR VBP104SR in millimeters




Drawing-No.: 6.541-5087.01-4

Issue: 1; 15.04.10


22106




## TAPING DIMENSIONS FOR VBP104S in millimeters



## TAPING DIMENSIONS FOR VBP104SR in millimeters



**REEL DIMENSIONS FOR VBP104S AND VBP104SR** in millimeters


21732


**SOLDER PROFILE**


Fig. 8 - Lead (Pb)-free Reflow Solder Profile  
acc. J-STD-020

**DRYPACK**

Devices are packed in moisture barrier bags (MBB) to prevent the products from moisture absorption during transportation and storage. Each bag contains a desiccant.

**FLOOR LIFE**

Time between soldering and removing from MBB must not exceed the time indicated in J-STD-020:

Moisture sensitivity: level 3

Floor life: 168 h

Conditions:  $T_{amb} < 30\text{ °C}$ ,  $RH < 60\%$

**DRYING**

In case of moisture absorption devices should be baked before soldering. Conditions see J-STD-020 or recommended conditions:

192 h at  $40\text{ °C} (+ 5\text{ °C})$ ,  $RH < 5\%$

or

96 h at  $60\text{ °C} (+ 5\text{ °C})$ ,  $RH < 5\%$ .



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.