
Surface Mount Ceramic Chip Antennas for 1.575 GHz



VJ5101W157GXCMT chip antenna

The VJ5101W157 series are small form-factor, high-performance chip-antennas optimized for GPS applications.

Designed for GPS applications, the VJ5101W157GXCMT antenna shows a superb performance and excellent peak/ average gain, allowing longer ranges than similar GPS patch antennas.

DESCRIPTION

The VJ5101W157GXCMT ceramic chip antenna is a small form-factor, high-performance, chip-antenna designed for operation at 1.575 GHz. It allows manufacturers to design high quality products that do not bear the penalty of a large external antenna, and is designed to be assembled onto a PC board using a standard reflow process.

FEATURES

RoHS COMPLIANT

- Small outline (10 mm x 3.2 mm x 0.8 mm)
- 50 Ω unbalanced tuning interface
- Linear polarization
- Assembled onto a PCB in the standard reflow process
- Wide transmit / receive range
- High stability in temperature / humidity changes
- Excellent peak / average gain
- Wide operating temperature range (- 40 °C to + 85 °C)
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912

APPLICATIONS

- GPS L1 band
- Transmission / reception at 1.575 GHz

ELECTRICAL SPECIFICATIONS

Operating temperature: - 40 °C to + 85 °C

Frequency range (transmission / reception): 1575 MHz ± 50 MHz

Note

- Electrical characteristics at + 25 °C unless otherwise specified.

QUICK REFERENCE DATA

SERIES	FREQUENCY (MHz)	MAX. GAIN (dBi)	AVERAGE GAIN (dBi)	BANDWIDTH (- 10 dB) (MHz)	BANDWIDTH (- 3 dB) (MHz)
VJ5101W157GXCMT	1575	+ 2.5	- 1.60	50	110

CHIP ANTENNA PERFORMANCE


NOMINAL FREQUENCY (MHz)	NOMINAL IMPEDANCE (Ω)	1.575 GHz PEAK GAIN (dBi)	1.575 GHz AVERAGE GAIN (dBi)	1.575 GHz REFLECTED POWER LOSS	1.575 GHz INSERTION POWER LOSS	- 3 dB BANDWIDTH 1.575 GHz	- 3 dB REFLECTED POWER LOSS	- 10 dB BANDWIDTH 1.575 GHz	- 10 dB REFLECTED POWER LOSS
1575	50	- 1.60	+ 2.5	< - 15 dB	< 4 %	110	50 %	50	10 %
				< 3.2 %	< 0.14 dB		3 dB		0.46 dB


For technical questions, contact: chipantenna@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


FOOTPRINT, MECHANICAL, AND PCB DIMENSIONS

The antenna footprint and mechanical dimensions are presented in figure 7. Optimal tuning is adjusted according to PCB layout.

FIGURE	SYMBOL	DIMENSION (mm)
	L	10 ± 0.20
	W	3.2 ± 0.20
	T	0.80 ± 0.10
	A	0.80 ± 0.10




Layout Design




Antenna on Test Board (thickness 0.8 mm)

For technical questions, contact: chipantenna@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000



Antenna S11 on Test Board










Antenna VSWR on Test Board

For technical questions, contact: chipantenna@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

RADIATION PATTERN

Radiation pattern and gain were dependent on measurement board design. The specification of VJ5101W157GXCMT antenna was measured based on the PCB size and installation position as shown in the below figure test board




	VERTICAL	HORIZONTAL
Y - Z Plane Average Gain = 0.651 dBi	Peak Gain = - 6.92 dBi, Average Gain = - 12.58 dBi 	Peak Gain = 2.49 dBi, Average Gain = 0.44 dBi 
X - Z Plane Average Gain = - 3.82 dBi	Peak Gain = 1.27 dBi, Average Gain = - 4.23 dBi 	Peak Gain = - 8.51 dBi, Average Gain = - 14.30 dBi 
X - Y Plane Average Gain = - 2.93 dBi	Peak Gain = 1.42 dBi, Average Gain = - 3.37 dBi 	Peak Gain = - 7.87 dBi, Average Gain = - 13.13 dBi 


For technical questions, contact: chipantenna@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

SOLDERING CONDITION

Typical examples of soldering processes that provide reliable joints without any damage are given in figure 2.



PACKAGING



PLASTIC TAPE SPECIFICATIONS (Dimensions in mm)									
A_O	B_O	ØD	T	W	E	F	P_O	P_1	P_2
3.40 ± 0.10	10.20 ± 0.10	1.50 ± 0.10	1.00 ± 0.10	24 ± 0.30	1.75 ± 0.10	11.50 ± 0.10	4.00 ± 0.10	8.00 ± 0.10	2.00 ± 0.10

ORDERING INFORMATION	VISHAY MATERIAL	PACKAGING QUANTITY
VJ5101W157 Chip Antenna	VJ5101W157GXCMT	2000 pieces

For technical questions, contact: chipantenna@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

© 2022 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED